

Exhibit 20.1

Radiofrequency Radiation Guidelines Compliance Study

The instant application has been evaluated for potential of human exposure to non-ionizing radio frequency radiation. The guidelines set forth in OET Bulletin No. 65, August 1997, were used as the standard for this evaluation.

The proposed Peotone, IL 640 kHz facility will operate with a daytime power of 4.4 kW and a nighttime power of 1.6 kW. Both daytime and nighttime modes of operation will employ the same four tower array, however with alternate sets of operating parameters. Two (2) of the towers employ radiating elements 63.0° in length with 12.0° of top-loading or an overall electrical height of 75.0°. The two (2) remaining towers employ radiating elements 70.0° with 12.0° of top-loading or an overall electrical height of 82°. For operation on 640 kHz, the radiating elements will range from 0.208λ (wavelengths) to 0.228λ (wavelengths) for operation on 640 kHz.

Review of OET Bulletin No. 65, Supplement A, Section 1, Table 2 specifies that for 0.21-0.4 wavelength AM towers with an input power of 5.0 kW or less, the non-ionizing radiation will fall to safe levels at distances of 2 meters (6.6 feet) or more.

Fencing will be constructed meeting or exceeding this 2 meter (6.6 ft) level of protection. Access to area within the fences will be limited by means of locked gates. In addition to these measures, signs will be posted warning of the potential for exposure to excessive levels of non-ionizing radio frequency radiation.

In the event maintenance personnel are required to work within the restricted area, they will be advised to limit their work in the high RF field area to specified periods of time appropriate for compliance with the ANSI guidelines set forth in OET Bulletin No. 65, August 1997. If their work cannot be completed within the specified period of time, it is proposed to reduce power appropriately or shut down the operation of the station to permit completion of the assignment. There are no additional sources of non-ionizing radiation subject to the guidelines of OET Bulletin No. 65 at this location.