

ENGINEERING REPORT

FM Translator Minor Construction Permit Modification Application

for

W214BH – Mount Pleasant, MI

CP File No. BPFT-20091001ACQ

October, 2009

COPYRIGHT 2009

MUNN-REESE, INC.
Broadcast Engineering Consultants
Coldwater, MI 49036

TABLE OF CONTENTS

Discussion of Report

FM Booster/Fill-in Translator Requirements (See Discussion)

Interference Requirements

Exhibit 12.1 - Copy of Existing Antenna Structure Registration

Exhibit 12.2 - Vertical Plan of Antenna System and Support Tower

Exhibit 12.3 - Present vs Proposed Service Contour Study

Exhibit 12.4 - Proposed vs Primary Station Service Contour Study

Contour Overlap Requirements

Exhibit 12.5 - Tabulation of Proposed Allocation

Exhibit 12.6 - Directional Antenna Pattern Study

TV Channel 6 Protection Requirements (None)

Unattended Operation Requirements (See Discussion)

Multiple Translator Requirements (See Discussion)

RF Radiation Study Requirement

Exhibit 16.1 - RF Compliance Study

(Exhibit numbering is in response to FCC Online Form 349, Section III-A)

Discussion

This firm has been retained to prepare the required engineering report in support of a minor construction permit modification application for FM Translator W214BH, Mount Pleasant, MI, Construction Permit BPFT-20091001ACQ. Present W214BH is licensed under BLFT-20040217ABW for operation on 90.7 MHz with 100 watts of non-directional power with an antenna COR of 244 meters AMSL. Due to informal concerns over potential interference raised by WKKM.C – Harrison, MI CH214A, the applicant has opted to modify operating parameters to minor change I.F. Channel CH267D with 10 watts ERP at 250 meters AMSL utilizing a new directional antenna pattern. The Translator will rebroadcast new primary station WMHW-FM, Mount Pleasant, MI (Facility ID No. 9910) as a Fill-In Translator.

The existing tower bears Antenna Structure Registration Number 1002165. A copy of the existing ASR has been included in **Exhibit 12.1**. A copy of the vertical antenna system has been included in **Exhibit 12.2**. It has been determined the translator may be used in the area without interference to any existing FM broadcast station or translator operation. Allocation details are found in **Exhibit 12.5**. It is believed sufficient clearance exists precluding the need for additional contour protection showings. The applicant would like to note the use of the NGDC 30 second terrain database for all HAAT, allocation and contour showings.

The Translator site lies inside of the primary contour of WMHW-FM.L and WMHW-FM.C, and the 1 mV/m (60 dBu) contour of the proposed Translator is contained wholly within the WMHW-FM.L or WMHW-FM.C station primary contour. A map of the proposed service area in relation to the primary station service contour has been included in **Exhibit 12.4**.

Regarding protection of international concerns, the present facility is and will remain within 320 km from the common border between the United States and Canada. However full protection will be afforded all Canadian concerns as the worst case proposed 34 dBu f(50:10) interference contour falls entirely over domestic soil. Documentation of the 34 dBu f(50:10) contour will be supplied upon request.

The proposed operating parameters have been changed from the licensed values, however the proposed service contour serves a portion of the present service area as seen in **Exhibit 12.3**.

RADIATION PROTECTION: The Commission requires an engineering study regarding compliance with the guidelines for human protection from radiofrequency radiation. This report section is in response to that provision of the Rules. The current Federal Communications Commission guidelines for RF radiation protection are set forth in OET Bulletin No. 65 (Edition 97-01), and the accompanying Supplement A, (Edition 97-01).

Discussion (continued)

The FM Broadcast facility proposed in this application will not produce human exposure to radiofrequency radiation in excess of the applicable safety standards specified in §1.1307(b)(3) of the Commission's rules concerning RF contributors of less than 5%. **Exhibit 16.1** provides the details of the study that was made to demonstrate compliance. The facility is properly marked with signs, and entry is restricted by means of fencing with locked doors and/or gates. Any other means as may be required to protect employees and the general public will be employed.

In the event work would be required in proximity to the antenna such that the person or persons working in the area would be potentially exposed to fields in excess of the guidelines set forth in OET Bulletin No. 65 (Edition 97-01), the transmitter power will be reduced or the station will cease operation during the critical period.

DISTANCES TO CONTOURS: The following tabulation of the distances to the proposed service contours results from calculations performed in accordance with §73.313(d) and §73.333 Figure 1.

N. Lat. = 433433.0 W. Lng. = 844629.0 HAAT and Distance to Contour, FCC, FM 2-10 Mi, 51 pts Method - NGDC 30 SEC						
Azi.	AV EL	HAAT	ERP kW	dBk	Field	60-F5
000	234.6	15.4	0.0100	-20.00	1.000	3.15
030	224.0	26.0	0.0086	-20.63	0.930	3.03
060	219.0	31.0	0.0053	-22.73	0.730	2.76
090	217.5	32.5	0.0019	-27.13	0.440	2.23
120	221.8	28.2	0.0006	-32.04	0.250	1.59
150	235.3	14.7	0.0005	-33.15	0.220	1.61
180	245.8	4.2	0.0005	-32.77	0.230	1.51
210	256.4	-6.4	0.0005	-33.15	0.220	1.61
240	270.4	-20.4	0.0006	-32.04	0.250	1.59
270	257.1	-7.1	0.0019	-27.13	0.440	2.15
300	254.1	-4.1	0.0053	-22.73	0.730	2.72
330	251.7	-1.7	0.0086	-20.63	0.930	3.03

Ave El= 240.64 M HAAT= 9.36 M AMSL= 250 M