

Non-Interference Compliance

Regarding Facility id 145133

Channel 270

Description of Exhibit 13 Contents

This exhibit demonstrates that the proposed facility complies with contour overlap and interference protection provisions in all of the applicable rule sections and that this application for a construction permit is in full compliance with 47 C.F.R. § 74.1204.

Let it be noted that should any actual real world interference occur, the applicant acknowledges that it will promptly suspend operation of this translator in accordance with 47 C.F.R. § 74.1203.

Page 2 of this exhibit is an explanation of the method used to demonstrate compliance with contour overlap and interference provisions based on 47 C.F.R. § 74.1204(d), which states:

[A]n application otherwise precluded by this section will be accepted if it can be demonstrated that no actual interference will occur due to intervening terrain, lack of population or such other factors as may be applicable.

Page 3 of this exhibit contains the tabulated data from the interference analysis, which shows all stations whose protected contours come within 50 km of the 34 dBμ F(50,10) contour of the proposed translator. These tabulated values were calculated using data from the FCC's CDBS files and 30 arc second terrain data. The column labeled "Adj" shows the number of channels difference between the entry and the proposed translator. The column labeled "Dist" shows the distance in km. The column labeled "Overlap" shows the area of contour overlap in square kilometers.

Page 4 of this exhibit is a portion of a USGS 1:24,000 scale 7.5 minute quadrangle at full scale with the calculated area of interference overlaid. The sheet includes the quadrangle name and measurement scale at the bottom-left corner (note: "Mt" refers to meters). The area of interference was calculated using the free space equation and 120 radials.

Page 5 of this exhibit is an aerial photo of the vicinity surrounding the proposed translator's tower site.

Note: There are no occupied buildings or major roads within the zone of predicted interference so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Compliance with 47 C.F.R. § 74.1204(d)

All authorized second and third adjacent stations with which the proposed translator has contour overlap are tabulated below. Column four show the station's signal level at the proposed translator's tower site, and column five gives the minimum value within the entire standard interfering contour of the proposed translator (100 dBμ for most classes, 94 for class B, 97 for class B1). The minimum second or third adjacent F(50,50) contour within the proposed translator's standard interfering contour was used to calculate the proposed translator's actual "worst-case" interfering contour.

Application_id	File Number	Callsign	Contour at Tower	Min. Contour
1327092	BLH20090820ABV	KJJJ	71.1	70.9
1352536	BLFTB20100108ABT	KJJJ-FM2	82.6	74.2
1601224	BLH20131118BJB	KXMK	61.9	61.9
Minimum F(50,50) Contour of Adjacent Station within Proposed Translator's Standard Interfering Contour				61.9

FCC 02-244 at Section II.A.5 states that "when demonstrating that 'no actual interference will occur due to . . . other factors,' pursuant to Section 74.1204(d), an applicant may use the undesired-to-desired signal ratio method." The undesired-to-desired ratio for second and third adjacent stations required by § 74.1204(a) is 40 dB. Since the minimum protected contour strength within the proposed translator's standard interference contour is **61.9 dBμ**, this makes the proposed translator's worst-case interfering contour **101.9 dBμ**. By the free-space equation, this contour is calculated to extend a maximum of **360.9 m** from the transmit antenna.

The interfering contour of the proposed translator was calculated for 120 radials and plotted on the pertinent portion of a USGS quadrangle (page 4 of this exhibit). As demonstrated on the quadrangle, there are no populated structures or highways within the area of interference (Note: FCC 02-244 at Section II.A.6 states that USGS quadrangles "have been recognized as acceptable to demonstrate lack of population").


Note: There are no occupied buildings or major roads within the zone of predicted interference so a lack of population has been demonstrated within the area of interference and this application is therefore in full compliance with 47 C.F.R. § 74.1204.

Antenna Manufacturer: ERI
Antenna Model: LPX-1E
CORAGL: 10 m
Maximum ERP: 0.041 kW
Interfering Contour: 101.9 dBμ
Max Int. Contour Distance: 360.9 m

Adjacent Channel Study **For Station NEW, Facility_id: 145133**

Co-channel through third adjacent:

App_id	Fac_id	File_Number	Call	Licensee	Class	City	State	Status	ERP	RCAMSL	Char	Adj	Dist	Overlap
1352536	181248	BLFTB-20100108ABT	KJJJ-FM2	STEVEN M. GREELEY	D	KINGMAN	AZ	LIC	0.5	2352	272	2	10.2	0.2447
1327092	63410	BLH-20090820ABV	KJJJ	STEVEN M. GREELEY	C1	LAUGHLIN	NV	LIC	17	1367	272	2	45.4	0.2447
1601224	183358	BLH-20131118BJB	KXMK	COCHISE MEDIA LICENSES, LLC	C2	OATMAN	AZ	LIC	2.2	1352	267	3	45.4	0.2447
174349	9036	BLFT-19920608TA	K268AC	CAMERON BROADCASTING, INC.	D	KINGMAN	AZ	LIC	0.01	2569	268	2	13.5	0
1569953	156670	BNPFT-20130821AAI	K269GB	DONALD F. HENDREN	D	CALNEVAIR	NV	CP	0.25	1333	269	1	45.4	0
1570828	150783	BNPFT-20130826ADI	K273CK	DONALD F. HENDREN	D	PEACH SPRINGS	AZ	CP	0.075	1825	273	3	51.8	0
1570817	152227	BNPFT-20130826ACI	K269GE	DONALD F. HENDREN	D	KINGMAN	AZ	CP	0.075	1725	269	1	56	0
1570821	156491	BNPFT-20130826ACI	K270CB	DONALD F. HENDREN	D	KINGMAN	AZ	CP	0.25	645	270	0	67.2	0
1352532	178460	BLFTB-20100108ABL	KJJJ-FM1	STEVEN M. GREELEY	D	LAKE HAVASU CI	AZ	LIC	1	1442	272	2	76.7	0
1487019	55503	BLH-20120214ACK	KWID	LOTUS BROADCASTING CORP.	C0	LAS VEGAS	NV	LIC	47	1370	270	0	131.5	0



Facility id: 145133;
Area of Interference;

