

Exhibit #29

R.F. RADIATION COMPLIANCE STATEMENT

WVPI
Channel 282
Charlotte Amalie, VI

October 2002

The proposed eight bay, circularly polarized antenna will be energized such that it produces 44 kW effective radiated power from a center of radiation of 61 meters above ground. Using the formulas expressed in the OET Bulletin, No. 65, August 1997, "Evaluating Compliance with F.C.C. Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", published by the Federal Communication Commission's Office of Science and Engineering, and then by applying a combination of the element and array pattern as defined in E.P.A. study PB85-245868 ("**Engineering Assessment of the Potential Impact of the Federal Radiation Protection Guidance on the AM, FM and TV Broadcast Services**") the predicted level of RF non-ionization emissions at a position of 2 meters above ground (head-height) for the proposed 8-bay ERI LPX (Type #3) antenna is 25.338 microwatts per square centimeter, which is 2.534 percent of the maximum for an controlled area and 12.667 percent for an uncontrolled area.

This is the only RF source on the tower or within the immediate vicinity.

The applicant will protect workers on the tower by either reducing ERP or terminating transmission.

Consequently, it appears that the proposed FM station, when using the antenna listed above, will be in full compliance with the Commission's human exposure to radiofrequency electromagnetic field rules and regulations.