

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: WNWI Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WRYT	383.0	30.9	19.7	214.6	157.003	6.7372	6.7372
WKJK	401.8	337.9	18.8	182.4	148.256	5.4070	8.6386
WTIC	1230.3	274.3	3.9	1070.6	23.304	4.9898	9.9762
KRLD	1255.9	36.6	3.7	692.8	28.565	3.9583	10.7328
WTSO *	203.5	137.1	49.1	205.3	281.154	1.1545	

* - indicates an adjacent channel station.

Point: WKII Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WAPI	874.0	146.4	7.4	1132.8	57.164	12.9510	12.9510
WHYZ	891.1	177.3	7.2	834.2	55.232	9.2146	15.8945
WFLI	958.1	159.8	6.4	772.5	49.520	7.6512	17.6402
WINA	1285.9	195.9	3.5	1011.9	30.268	6.1256	18.6735
CBA	2619.3	221.7	.0	2674.3	6.700	3.5834	

* - indicates an adjacent channel station.

Point: KOPY Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
XENVA2e	219.9	345.1	32.7	169.6	285.418	9.6791	9.6791
KNX	2045.6	103.8	.0	2833.6	14.615	8.2827	12.7392
KRLD *	584.9	194.0	12.5	3710.7	99.994	7.4210	14.7431
KFDI	1112.2	183.8	4.9	526.6	39.016	4.1090	15.3050
WAPI	1245.1	241.9	3.8	551.0	33.155	3.6538	

* - indicates an adjacent channel station.

Point: KENR Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
KRLD *	340.8	160.6	22.1	2527.1	187.909	9.4974	9.4974
KOPY	353.7	45.3	21.3	225.9	183.315	8.2807	12.6004
KNX	2196.2	95.0	.0	2833.6	12.451	7.0559	14.4415
KFDI	880.6	168.2	7.3	603.8	55.211	6.6669	15.9061
WDIA	777.5	222.6	15.3	440.1	66.984	5.8964	16.9638
WAPI	900.4	246.2	7.1	492.7	54.246	5.3457	17.7862
XENVA2e	500.2	23.1	14.9	205.5	126.593	5.2034	18.5317
XENVA	999.3	15.4	5.9	213.3	52.562	2.2422	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: WAPI Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
KNX	2896.4	81.8	.0	2833.6	6.661	3.7751	3.7751
CBA	2338.3	241.4	.0	2674.3	6.802	3.6378	5.2426
WHYZ	436.7	250.9	17.3	83.1	142.450	2.3673	5.7523
KOPY	1245.1	56.2	3.8	299.9	33.155	1.9889	6.0864
WFLI	218.6	221.0	32.9	32.9	280.321	1.8422	6.3591
KHMO	784.1	148.1	8.6	146.1	62.511	1.8270	6.6164
WKII	874.0	328.8	7.4	150.1	57.164	1.7156	6.8352
CHOK	1112.6	202.6	9.6	235.8	33.589	1.5842	

* - indicates an adjacent channel station.

Point: KNX Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
XEZO	769.4	328.9	8.9	136.7	71.871	1.9655	1.9655
KRLD *	2014.2	279.0	.0	4152.3	14.164	1.1762	2.2906
XEOBS	1070.1	313.5	5.2	128.9	44.393	1.1447	2.5607
XE-c	1659.4	318.2	1.2	199.0	23.328	.9287	2.7239
XESP	2086.6	317.9	.0	280.2	16.323	.9146	2.8734
XE-d	1920.6	311.7	.0	215.2	18.056	.7770	2.9766
XENVA	2458.1	320.4	.0	260.5	12.778	.6657	

* - indicates an adjacent channel station.

Point: WHYZ Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WIBC	657.4	147.2	10.9	1994.9	79.566	31.7455	31.7455
WFLI	265.1	92.2	27.9	582.2	239.730	27.9165	42.2741
WAPI	436.7	68.4	17.3	462.7	142.450	13.1822	44.2818
WINA	499.0	226.2	15.0	313.9	117.991	7.4083	

* - indicates an adjacent channel station.

Point: WNCT Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WINA	292.5	160.5	25.5	1076.0	216.908	46.6805	46.6805
WIBC	921.5	118.8	6.8	2615.9	46.466	24.3104	52.6314
WFLI	722.5	82.8	9.6	652.9	71.562	9.3449	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: WFLI Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WIBC	553.0	170.6	22.1	424.9	101.814	8.6528	8.6528
WAPI	218.6	40.2	41.4	146.6	280.321	8.2202	11.9349
WHYZ	265.1	273.9	27.9	99.8	239.730	4.7848	12.8583
CBA	2121.4	242.2	.0	2674.3	7.993	4.2753	13.5504
KNX	3013.3	78.1	.0	2833.6	5.894	3.3400	

* - indicates an adjacent channel station.

Point: WDIA Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
KNX	2589.8	78.5	.0	2833.6	8.219	4.6581	4.6581
WAPI	342.9	304.7	22.0	115.2	187.177	4.3107	6.3466
KHMO	499.4	165.7	14.9	172.4	117.494	4.0520	7.5299
CBA	2433.8	249.5	.0	2674.3	5.736	3.0678	8.1308
WHYZ	688.8	275.4	10.2	137.0	77.309	2.1179	8.4021
WIBC	612.6	212.9	11.8	110.2	88.280	1.9460	

* - indicates an adjacent channel station.

Point: KFDI Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
KNX	1939.4	71.1	.0	2833.6	14.249	8.0751	8.0751
KRLD	* 545.1	353.6	13.6	1759.7	107.703	3.7906	8.9205
CBA	2830.7	262.8	.0	2674.3	3.417	1.8274	

* - indicates an adjacent channel station.

Point: WINA Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WIBC	709.2	104.5	9.9	1615.9	68.200	22.0407	22.0407
CHOK	623.8	147.6	11.6	606.2	79.412	9.6274	24.0516
CBA	1439.1	237.1	2.5	2654.6	16.471	8.7448	25.5920
KYW	* 359.1	232.5	21.0	1499.0	170.332	5.1066	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: WIBC Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
CBA	1880.1	256.7	.1	2673.2	8.443	4.5138	4.5138
KNX	2906.9	67.2	.0	2833.6	5.676	3.2169	5.5428
WAPI	713.7	3.8	9.8	220.0	71.610	3.1506	6.3756
KHMO	430.1	83.5	28.1	105.7	137.004	2.8955	7.0023
CHOK	468.7	227.2	26.0	103.9	117.283	2.4367	7.4141
WTSO	418.1	142.9	18.1	83.3	137.005	2.2816	7.7573
KYW *	945.3	272.6	6.5	2730.6	41.110	2.2452	8.0757
WFLI	553.0	351.2	19.2	83.0	101.814	1.6897	

* - indicates an adjacent channel station.

Point: KHMO Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
KNX	2476.7	67.2	.0	2833.6	8.289	4.6973	4.6973
WAPI	784.1	330.8	8.6	295.0	62.511	3.6880	5.9721
CBA	2277.1	261.4	.0	2674.3	5.398	2.8870	6.6333
WIBC	430.1	266.8	28.1	104.4	137.004	2.8617	7.2243
WFLI	736.1	315.6	9.4	142.2	67.714	1.9262	7.4767
WDIA	499.4	346.5	24.4	81.6	117.494	1.9186	7.7189
WTSO	412.0	205.4	29.2	53.8	140.776	1.5146	

* - indicates an adjacent channel station.

Point: WKOK-C Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
CBA	1132.7	244.0	4.7	2637.0	24.132	12.7273	12.7273
KYW *	158.5	303.6	41.9	1397.8	335.042	9.3665	15.8024
CHOK	507.2	114.3	24.1	239.6	102.857	4.9294	16.5534
WTIC *	349.6	254.8	21.6	883.0	168.342	2.9728	

* - indicates an adjacent channel station.

Point: WTSO Frequency: 1070 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
-----	-----	-----	-----	-----	-----	-----	-----
WIBC	418.1	324.9	18.1	208.2	137.005	5.7041	5.7041
KHMO	412.0	24.0	18.3	200.9	140.776	5.6571	8.0337
KNX	2708.2	59.4	.0	2833.6	6.218	3.5236	8.7724
CBA	1973.2	269.0	.0	2674.3	6.356	3.3995	9.4081
CHOK	569.0	273.5	21.5	172.3	84.799	2.9227	9.8516
WAPI	1070.6	349.4	5.2	290.9	36.132	2.1024	
KYW *	1212.0	290.0	4.0	3598.2	24.380	1.7545	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: TGLU Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	2116.4	158.5	.4	3470.2	3.536	2.4540	2.4540
XE-e	623.9	105.5	15.7	267.9	43.180	2.3132	3.3724
XEOB	475.9	126.2	20.8	105.2	51.167	1.0763	

* - indicates an adjacent channel station.

Point: HRID Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	2114.8	152.0	.4	3240.6	3.543	2.2963	2.2963
XE-e	819.5	95.1	11.3	274.0	33.556	1.8390	2.9419
XEOB	629.2	107.4	15.5	109.5	42.921	.9398	

* - indicates an adjacent channel station.

Point: XE-e Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1822.1	174.8	1.9	3867.4	14.034	10.8546	10.8546
XE-f	637.0	119.4	15.3	289.8	106.872	6.1953	12.4981
XECN	799.9	124.1	11.7	209.0	86.410	3.6113	

* - indicates an adjacent channel station.

Point: XEUU Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1671.2	206.6	2.8	4151.6	18.570	15.4194	15.4194
XEJLV	223.1	134.1	40.1	204.4	213.584	8.7307	17.7196
XE-f	353.9	267.2	27.6	257.1	154.926	7.9660	

* - indicates an adjacent channel station.

Point: XE-f Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1539.9	194.7	3.6	4095.2	24.428	20.0081	20.0081
XECN	175.0	143.1	47.2	128.9	260.956	6.7272	
XEJLV	528.7	103.9	18.7	267.4	120.527	6.4465	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: XETUL Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1489.7	190.0	4.0	4056.1	26.889	21.8132	21.8132
XE-f	131.7	78.4	55.2	148.5	343.698	10.2079	

* - indicates an adjacent channel station.

Point: XECN Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1432.5	200.1	4.4	4110.3	29.992	24.6554	24.6554
XE-f	175.0	323.5	47.2	182.6	260.956	9.5299	

* - indicates an adjacent channel station.

Point: XEJLV Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1603.9	214.1	3.2	4153.5	21.352	17.7371	17.7371
XE-f	528.7	285.6	18.7	282.2	120.527	6.8021	

* - indicates an adjacent channel station.

Point: XEXK1 Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1375.7	183.6	4.8	3969.3	33.411	26.5237	26.5237
XE-f	323.7	67.3	29.9	249.8	164.579	8.2237	

* - indicates an adjacent channel station.

Point: CMMQ Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
WVCG	861.6	132.9	10.6	212.3	31.713	1.3466	1.3466
WTIC	2387.6	184.3	.0	2542.4	2.579	1.3111	1.8795
KRLD	2596.6	116.9	.0	1860.4	2.040	.7589	

* - indicates an adjacent channel station.

Point: XEDC Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1344.9	205.9	5.1	4116.1	35.410	29.1498	29.1498
XE-f	339.4	323.4	28.7	253.7	159.367	8.0872	

* - indicates an adjacent channel station.

MUNN-REESE, INC.

Broadcast Engineering Consultants
Coldwater, MI 49036

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: XE-g Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1122.8	192.1	7.1	3972.9	52.608	41.8016	41.8016
XE-f	421.1	19.8	23.5	269.6	138.783	7.4842	

* - indicates an adjacent channel station.

Point: CMAM Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
WVCG	537.0	223.5	18.4	350.7	47.510	3.3322	3.3322
KRLD	1710.2	130.9	2.5	2389.9	6.840	3.2695	4.6683
XE-e	1312.2	59.7	5.3	279.6	14.984	.8379	

* - indicates an adjacent channel station.

Point: XEPAB Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1650.5	237.5	2.9	4150.0	19.366	16.0736	16.0736
XE-h	224.7	217.5	39.9	150.2	212.428	6.3825	

* - indicates an adjacent channel station.

Point: WVCG Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1748.2	112.8	.8	1707.5	19.036	6.5008	6.5008
WTIC	1918.3	204.1	.0	1661.8	14.356	4.7711	8.0637
WKJK	1481.8	158.9	2.2	713.4	24.078	3.4354	8.7650
XE-e	1822.6	53.5	.4	281.1	22.607	1.2711	

* - indicates an adjacent channel station.

Point: XE-h Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1433.5	239.7	4.4	4127.2	29.936	24.7103	24.7103
XEJLV	686.7	326.7	14.0	276.1	100.879	5.5707	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: XEDT Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1096.9	245.7	7.4	4018.0	55.144	44.3131	44.3131
XE-h	361.1	35.1	27.1	182.9	153.075	5.5997	

* - indicates an adjacent channel station.

Point: XENVA2 Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	933.1	264.8	9.5	3941.8	71.287	56.2002	56.2002
XE-h	707.0	19.7	13.6	207.1	98.324	4.0725	

* - indicates an adjacent channel station.

Point: KRLD Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
XENVA2g	933.1	79.5	6.7	213.6	51.645	2.2066	2.2066
XENVA2f	933.1	79.5	6.7	212.6	51.645	2.1964	3.1134
WTIC	2317.2	252.5	.0	1142.6	8.375	1.9139	3.6547
XE-g	1122.8	11.1	4.8	208.1	41.965	1.7465	4.0506
XE-f	1539.9	13.1	1.9	304.9	26.887	1.6395	4.3698
XEJLV	1603.9	30.2	1.5	287.3	24.913	1.4317	4.5983
XESAC1	935.9	25.8	6.6	132.6	53.558	1.4207	4.8128
XEDC	1344.9	23.3	3.1	215.7	32.354	1.3960	5.0112
XECN	1432.5	18.0	2.5	215.1	29.712	1.2780	5.1716
KFDI *	545.1	173.2	13.6	582.3	107.703	1.2543	

* - indicates an adjacent channel station.

Point: XEDY1 Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	1701.7	274.0	2.6	4135.5	17.462	14.4429	14.4429
XENVA2g	794.7	279.4	11.8	209.2	87.025	3.6411	
XENVA2f	794.7	279.4	11.8	208.2	87.025	3.6243	

* - indicates an adjacent channel station.

Point: KSCO Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	2346.1	288.2	.0	4081.0	10.163	8.2949	8.2949
XEPRS *	674.2	319.8	10.5	4295.6	82.602	7.0965	10.9163
KOTK	956.5	177.3	6.4	730.4	45.624	6.6644	12.7899
KNX *	476.6	317.4	15.7	2357.6	129.256	6.0946	14.1677
XEDY1	808.0	308.5	8.3	142.3	63.909	1.8187	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: WRYT Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	880.6	40.8	7.3	654.5	53.396	6.9896	6.9896
WTIC	1496.9	262.5	2.1	1027.5	17.323	3.5599	7.8440
KAAY *	497.8	22.7	15.0	1279.4	119.177	3.0495	8.4159
WKJK	366.8	278.3	32.3	60.2	168.994	2.0332	

* - indicates an adjacent channel station.

Point: WKJK Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
WTIC	1172.3	255.1	4.4	1072.5	27.909	5.9866	5.9866
WIBC *	188.8	165.8	44.5	756.9	306.479	4.6394	7.5738
KRLD	1147.2	55.3	4.6	634.2	34.787	4.4125	8.7654
WRYT	366.8	95.7	32.3	50.5	168.994	1.7071	

* - indicates an adjacent channel station.

Point: WTIC Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
WBAL *	428.3	50.2	17.6	3342.1	133.480	8.9219	8.9219
CBA *	803.6	236.8	8.3	2557.0	44.641	2.2829	9.2094
KRLD	2317.2	57.9	.0	643.6	8.375	1.0781	

* - indicates an adjacent channel station.

Point: KOTK Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	2615.7	310.1	.0	3703.3	6.668	4.9385	4.9385
KMPS *	204.3	181.4	34.7	608.2	282.970	3.4418	6.0195
XEPRS *	1531.9	343.9	1.9	5121.0	21.372	2.1889	6.4051
KNX *	1347.3	346.1	3.1	2802.3	26.396	1.4794	
KSCO	956.5	357.6	6.4	130.5	45.624	1.1909	

* - indicates an adjacent channel station.

Point: KVNI Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
KRLD	2349.1	320.1	.0	3376.7	7.845	5.2984	5.2984
KOTK	496.4	60.5	15.0	199.9	106.495	4.2572	6.7969
CKSA	783.2	220.0	8.6	142.7	39.981	1.1413	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: CKSA Frequency: 1080 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
KRLD	2498.0	338.8	.0	2628.5	5.696	2.9942	2.9942
KOTK	1238.4	42.0	6.0	224.4	43.023	1.9308	3.5627
WTIC	3026.2	307.7	.0	2051.9	3.523	1.4456	

* - indicates an adjacent channel station.

Point: KAAV Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
WTAM *	1188.3	234.7	4.2	2705.4	30.305	1.6397	1.6397
KRLD *	450.7	63.8	16.7	546.9	137.879	1.5082	2.2279
XENVA2h	1230.4	55.9	3.9	215.1	33.587	1.4449	2.6554
XEWL	1053.1	39.6	5.4	151.7	43.182	1.3102	2.9610
XEXE2	1754.0	25.6	.7	307.6	20.632	1.2691	3.2215
XELB1	1889.3	30.5	.1	343.7	18.327	1.2599	3.4591
XEMCA1	1500.8	21.3	2.1	215.5	25.995	1.1205	3.6361
XE-j	1936.3	26.3	.0	305.5	17.854	1.0909	3.7962
XE-i	2027.6	11.7	.0	305.5	17.044	1.0415	3.9365
XEAU	1258.0	35.9	3.7	147.6	32.943	.9727	

* - indicates an adjacent channel station.

Point: KKYN Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
KRLD *	482.0	287.5	15.5	3462.7	127.307	8.8164	8.8164
XENVA2h	605.1	15.2	12.0	208.9	95.650	3.9963	9.6799
KAAV	865.8	268.9	7.5	241.6	56.301	2.7201	10.0548
XEWL	760.2	345.3	9.0	149.9	70.164	2.1033	

* - indicates an adjacent channel station.

Point: NEW-1 Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
XEPRS	692.6	348.7	10.2	4462.9	79.243	70.7305	70.7305
KBOZ	1003.9	220.9	5.9	896.0	39.747	7.1228	

* - indicates an adjacent channel station.

EXHIBIT 15.2

Determination of Class B Nighttime RSS Limits

Point: KMXA Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
KAAY	1235.9	300.7	5.0	1190.8	29.964	7.1359	7.1359
KKYN	675.0	337.5	10.5	224.5	79.564	3.5727	7.9804
KRLD *	1039.7	318.7	5.5	3352.2	41.217	2.7633	8.4452
XENVA2h	1208.2	354.7	4.1	215.1	33.777	1.4527	

* - indicates an adjacent channel station.

Point: WBAL Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
WTAM *	462.3	115.7	16.2	2305.6	121.858	5.6191	5.6191
WTIC *	428.3	232.7	17.6	967.8	133.480	2.5837	6.1846
KAAY	1469.0	64.3	2.3	119.4	21.188	.5061	

* - indicates an adjacent channel station.

Point: WCAR Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
WTAM *	185.4	309.6	37.4	1064.3	300.719	6.4010	6.4010
KAAY	1153.6	39.2	9.1	252.4	31.457	1.5878	

* - indicates an adjacent channel station.

Point: KBOZ Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
KAAY	2009.5	313.2	.0	2722.7	10.619	5.7823	5.7823
XEPRS	1554.2	17.6	5.0	1165.1	20.259	4.7210	7.4647
KNZZ *	772.7	344.4	8.8	1961.8	59.204	2.3229	7.8178
KMXA	844.7	323.7	7.8	211.9	50.115	2.1235	8.1011
KKYN	1511.4	330.8	2.0	342.3	19.719	1.3499	

* - indicates an adjacent channel station.

Point: KMPS Frequency: 1090 kHz

Station Call	Distance (km)	Bearing (degs.)	Theta (degs.)	Radiation (mV/m)	SW Mult. (uV/m)	IF Level (mV/m)	RSS (mV/m)
<hr/>							
XEPRS	1724.3	346.4	.9	4936.8	16.716	16.5044	16.5044
CKRX	749.1	255.2	9.2	350.7	51.101	3.5840	

* - indicates an adjacent channel station.