

United States of America FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION LICENSE

Authorizing Official:

Official Mailing Address:

AUDACY LICENSE, LLC 2400 MARKET STREET 4TH FLOOR PHILADELPHIA PA 19103 Son Nguyen Supervisory Engineer Audio Division Media Bureau

Grant Date: November 01, 2007

This license expires 3:00 a.m. local time, August 01, 2013.

Facility Id: 59820

Call Sign: KRLD

License File Number: BZ-20070227AFK

This supersedes authorization of same date to corect the phasing and the tower orientation of the nighttime directional pattern. HKC 8/2/2016

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Hours of Operation: Unlimited

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

| Jan. | 7:30 AM | 5:45 PM | Jul. | 5:30 AM | 7:30 PM |
|------|---------|---------|------|---------|---------|
| Feb. | 7:15 AM | 6:15 PM | Aug. | 5:45 AM | 7:15 PM |
| Mar. | 6:45 AM | 6:30 PM | Sep. | 6:15 AM | 6:30 PM |
| Apr. | 6:00 AM | 7:00 PM | Oct. | 6:30 AM | 6:00 PM |
| Мау | 5:30 AM | 7:15 PM | Nov. | 7:00 AM | 5:30 PM |
| Jun. | 5:15 AM | 7:30 PM | Dec. | 7:15 AM | 5:15 PM |

Callsign: KRLD

Name of Licensee: AUDACY LICENSE, LLC Station Location: DALLAS, TX Frequency (kHz): 1080 Station Class: A Antenna Coordinates: Day 32 Deg 53 Min Latitude: Ν 25 Sec Longitude: 96 Deg 38 Min 44 Sec W Night Ν 32 Deg 53 Min Latitude: 25 Sec 96 Deg 38 Min 44 Sec Longitude: W Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules. Nominal Power (kW): Day: 50.0 Night: 50.0 Antenna Input Power (kW): Day: 50.0 Night: 52.5 Antenna Mode: Night: DA Day: ND (DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours) Current (amperes): Day: 22.6 Night: 32.4 Resistance (ohms): Day: 98.3 Night: 50 Non-Directional Antenna: Day Radiator Height: 144.8 meters; 187.5 deg Theoretical Efficiency: 394.29 mV/m/kw at 1km Antenna Registration Number(s): Day: Tower No. ASRN Overall Height (m) 1046896 1 Night: Tower No. ASRN Overall Height (m) 1046896 1 2 1046897

| Callaian, KRLD | | | | т | Licongo No . BZ-20070227AEK | | | |
|---|-------------------------|----------|---------|-------------|-----------------------------|-----------|--|--|
| Jalisign: KKUD | | | | Ц | icense No.: | DZ 200702 | | |
| DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM | | | | | | | | |
| Theoretical RMS (mV/m/km): | | | | Night | : 2758.9 | | | |
| Standard | Standard RMS (mV/m/km): | | | | | | | |
| Augmented RMS (mV/m/km): | | | | Night | :3051.46 | | | |
| Q Factor: | | | | Night: | 70.71 | | | |
| Theoreti | ical Param | eters: | | | | | | |
| Night Di | Irectional | Antenna: | | | | | | |
| Tower | Field | Phasing | Spacing | Orientation | Tower Ref | Height | | |
| 100. | 1 0000 | (Deg.) | (Deg.) | (Deg.) | Switcii " | (Deg.) | | |
| T | T.0000 | 0.000 | 0.0000 | 0.000 | 0 | 187.5 | | |

2 0.7300 -86.500 93.5000 237.750 0 187.5

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Augmentation Parameters:

| Aug No. | Central Azimuth (Deg. T) | Span (Deg.) | Radiation at Central Azimuth (mV/m @ 1 km) |
|------------|--------------------------------|----------------|--|
| 1 | 12.7 | 27.4 | 1184.00 |
| 2 | 26.4 | 27.2 | 852.95 |
| 3 | 40.0 | 20.0 | 678.66 |
| 4 | 50.0 | 15.4 | 643.74 |
| 5 | 57.5 | 14.6 | 643.74 |
| 6 | 65.0 | 14.6 | 643.74 |
| 7 | 80.4 | 30.6 | 740.30 |
| 8 | 102.7 | 44.6 | 1400.10 |
| 9 | 125.0 | 44.6 | 2172.60 |
| 10 | 147.7 | 44.6 | 3088.80 |
| 11 | 170.0 | 44.6 | 3798.10 |
| 12 | 192.7 | 44.6 | 4132.80 |
| 13 | 215.0 | 44.6 | 4197.80 |
| 14 | 237.0 | 44.6 | 4190.10 |
| 15 | 260.0 | 44.6 | 4197.80 |
| 16 | 282.7 | 44.6 | 4133.60 |
| 17 | 305.7 | 44.6 | 3809.50 |
| 18 | 327.7 | 44.6 | 3092.70 |
| 19 | 350.0 | 44.6 | 2118.20 |

Night Directional Operation:

| Twr. | Phase | Antenna Monitor |
|------|--------|----------------------|
| No. | (Deg.) | Sample Current Ratio |
| 1 | 0 | 1 |

Callsign: KRLD

Night Directional Operation:

Twr. PhaseAntenna MonitorNo. (Deg.)Sample Current Ratio2-860.925

Antenna Monitor: POTOMAC INSTRUMENTS AM-19D (210)

Sampling System Approved Under Section 73.68 of the Rules.

Monitoring Points:

Night Operation:

| Radial | Distance | From | Transmitter | Maximum | Field | Strength |
|----------|----------|------|-------------|---------|--------|----------|
| (Deg. T) | | (kM |) | | (mV/m) | |
| 58 | | 3.2 | 2 | | 209.5 | |

Special operating conditions or restrictions:

1 DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM No. and Type of Elements: Two uniform cross section, guyed, series excited steel towers.

Ground System consists of 120 equally spaced, buried copper wire radials 152.4 m in length, except where intersection radials are shortened and bonded, plus 120 interspersed radials 29 m in length about the base of each tower.

DESCRIPTION OF AND FIELD INTENSITY MEASURED AT MONITORING POINTS:

Direction of 58 True North: From the transmitter, turn right (north) on Saturn Road and go 0.28 miles to Miller Road. Turn right (east) on Miller Road and go 1.52 miles to Dairy Road. Turn left (north) go 0.84 miles to Glynn. Turn right (east) and go to the monitor point at the driveway of 1122 Glynn. The monitor point is point number 12 on the 58 degree radial 3.22 km.

*** END OF AUTHORIZATION ***