## **Federal Communications Commission**

## FM BROADCAST STATION CONSTRUCTION PERMIT

## **Permittee**

CALVARY CHAPEL PEARL HARBOR 94-1044 Waipio Uka St Waipahu, HI, 96797

Call Sign	Facility ID
	767193

File Number 0000167437	TED STA	
Filing Date 11/09/2021	<b>Grant Date</b> 01/13/2022	Expiration Date 36 months after the grant date

Community of License	Frequency (MHz)	Station Channel	Station Class
City: Soledad State: CA	90.5	213	B1
Hours of Operation: Unlimited	E A ST		·

Transmitter  Certified for Compliance. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.	Transmitter Output Power As required to achieve authorized ERP.
Antenna Type Directional	Antenna Coordinates (NAD 83)  Latitude 36-36-44.6 N  Longitude 121-3-53.2 W
Major Lobe Directions Not Applicable	1

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective Radiated Power in the Horizontal Plane (kW)	.250	.250

Height of Radiation Center Above Ground (meters)	12	12
Height of Radiation Center Above Mean Sea Level (meters)	1193.7	1193.7
Height of Radiation Center Above Average Terrain (meters)	523.11	523.11

_	Overall Height of Antenna Structure Above Ground (meters) See the registration for this antenna structure.
Obstruction Marking and Lighting Specifications for Antenna Structure	

See the registration for this antenna structure.



## **Special Operating Conditions or Restrictions**

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the
  installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include
  a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and
  list the qualifica- tions of the certifying engineer.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee must submit a certification executed by a
  licensed surveyor showing that the FM directional antenna system has been oriented at the azimuth(s)
  specified in the directional antenna proof of performance. This certification must include a description of the
  method used by the surveyor to determine the azimuth(s) of the installed directional antenna system and the
  accuracy of that determination.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an exhibit demonstrating that
  the measured directional antenna pattern complies with the appropriate community coverage provisions of 47
  C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. Section 73.316(c)(2)(ix)(B)).
- The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit. A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power: 0.250 kilowatt. Principal minima and their associated field strength limits: 300 degrees True: 0.0135 kilowatt.
- Permittee has specified use of the antenna listed below to demonstrate compliance with the FCC radiofrequency electromagnetic field exposure guidelines. If any other type or size of antenna is to be used with the facilities authorized herein, THE AUTOMATIC PROGRAM TEST PROVISIONS OF 47 C.F.R. SECTION 73.1620 WILL NOT APPLY. In this case, a FORMAL REQUEST FOR PROGRAM TEST AUTHORITY must be filed in conjunction with FCC application for license, BEFORE program tests will be authorized. The request must include a revised RF field showing to demonstrate continued compliance with the FCC guidelines. Antenna Type (EPA Type 2), 2 sections.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules(See Section 83.875).

Pursuant to Section 73.3598, this Construction Permit will be subject to automatic forfeiture unless construction is complete and application for license is filed prior to expiration.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

