Federal Communications Commission

FM BROADCAST STATION CONSTRUCTION PERMIT

Permittee

Crossroads Worship Center PO Box 66 Braggadocio, MO, 63826

Call Sign	Facility ID
	762511

File Number 0000166716	TED STA	
Filing Date 03/03/2022	Grant Date 04/26/2022	Expiration Date 36 months after the grant date

Community of License	Frequency (MHz)	Station Channel	Station Class
City: Hayti State: MO	88.1	201	C2
Hours of Operation: Unlimited	A QQ		<u>'</u>
Facility Type: Noncommercia	ll Educational		


Transmitter Certified for Compliance. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.	Transmitter Output Power As required to achieve authorized ERP.
Antenna Type Directional	Antenna Coordinates (NAD 83) Latitude 36-29-55 N Longitude 89-51-16 W
Major Lobe Directions	

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective Radiated Power in the Horizontal Plane (kW)	27.5	27.5

Not Applicable

Height of Radiation Center Above Ground (meters)	99	99
Height of Radiation Center Above Mean Sea Level (meters)	182	182
Height of Radiation Center Above Average Terrain (meters)	98	98

_	Overall Height of Antenna Structure Above Ground (meters) See the registration for this antenna structure.
Obstruction Marking and Lighting Specifications for Antenna Structure	





Special Operating Conditions or Restrictions

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

- Pursuant to 47 CFR Sections 73.7002(c) and 73.7005(b) the permittee/licensee is required to construct and
 operate for a period of four years of on-air operations technical facilities substantially as proposed and shall
 not downgrade service to the area on which the preference was based.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the
 installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include
 a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and
 list the qualifica- tions of the certifying engineer.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee must submit a certification executed by a
 licensed surveyor showing that the FM directional antenna system has been oriented at the azimuth(s)
 specified in the directional antenna proof of performance. This certification must include a description of the
 method used by the surveyor to determine the azimuth(s) of the installed directional antenna system and the
 accuracy of that determination.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an exhibit demonstrating that
 the measured directional antenna pattern complies with the appropriate community coverage provisions of 47
 C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. Section 73.316(c)(2)(ix)(B)).
- The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit. A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power: **** 27.5 kilowatts. **** Principal minima and their associated field strength limits: **** 190-260 degrees True: 10.0 kilowatts ****

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules(See Section 83.875).

Pursuant to Section 73.3598, this Construction Permit will be subject to automatic forfeiture unless construction is complete and application for license is filed prior to expiration.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.



Page 4 of 4