Federal Communications Commission

FM BROADCAST STATION CONSTRUCTION PERMIT

Permittee Smile FM 172 N Cedar St Imlay City, MI, 48444

Call Sign	Facility ID
	766878

File Number 0000218628	This Permit Modifies License File No. 0000167796	
Filing Date 07/28/2023	Grant Date 09/22/2023	Expiration Date 04/08/2025

Community of License City: Litchfield State: MI	Frequency (MHz) 88.9	Station Channel 205	Station Class A
Hours of Operation: Unlimited		7887	
Facility Type: Noncommercial Edu	cational		

Transmitter Certified for Compliance. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.	Transmitter Output Power As required to achieve authorized ERP.
Antenna Type Directional	Antenna Coordinates (NAD 83) Latitude 41-53-41.6 N Longitude 84-39-53.3 W
Major Lobe Directions	

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective Radiated Power in the Horizontal Plane (kW)	1	1
Height of Radiation Center Above Ground (meters)	91	91

Not Applicable

Height of Radiation Center Above Mean Sea Level (meters)	451.0	451.0
Height of Radiation Center Above Average Terrain (meters)	116	116

Antenna Structure Registration Number 1321579	Overall Height of Antenna Structure Above Ground (meters) See the registration for this antenna structure.
Obstruction Marking and Lighting Specific	ations for Antenna Structure
See the registration for this antenna structure.	



Special Operating Conditions or Restrictions

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. The proof-of-performance may also be accomplished using computer modeling, assuming it satisfies all of the requirements of 47 C.F.R. Section 73.316. (See 47 C.F.R. Section 73.316(c)(2)(iv)). Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifica- tions of the certifying engineer.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee must submit a certification executed by a
 licensed surveyor showing that the FM directional antenna system has been oriented at the azimuth(s)
 specified in the directional antenna proof of performance. This certification must include a description of the
 method used by the surveyor to determine the azimuth(s) of the installed directional antenna system and the
 accuracy of that determination.
- BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an exhibit demonstrating that
 the measured directional antenna pattern complies with the appropriate community coverage provisions of 47
 C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. Section 73.316(c)(2)(ix)(B)).
- The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit. A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power: 1 kilowatts. Principal minima and their associated field strength limits: 100 degrees True: 0.050 kilowatts.
- Pursuant to 47 CFR Sections 73.7002(c)(1) and 73.7005(b) the permittee/licensee is required to construct and
 operate for a period of four years of on-air operations technical facilities substantially as proposed and shall
 not downgrade service to the area on which the preference was based.
- The RMS of the composite measured relative field horizontal plane directional antenna pattern must encompass at least 85% of the RMS of the composite relative field horizontal plane directional antenna pattern authorized by this construction permit.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules(See Section 83.875).

Pursuant to Section 73.3598, this Construction Permit will be subject to automatic forfeiture unless construction is complete and application for license is filed prior to expiration.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

