

## United States of America FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

LAKE ERIE COLLEGE OF OSTEOPATHIC MEDICINE	, Il Son Nguyen		
1858 WEST GRANDVIEW BLVD.	Supervisory Engineer		
ERIE PA 16509	Audio Division		
	Media Bureau		
	Grant Date: October 27, 2015		
Facility Id: 27663	This permit expires 3:00 a.m.		
Call Sign: WSRQ	local time, 36 months after the		
Permit File Number: BP-20150120AIX	grant date specified above.		

This Permit Modifies Permit No.: BL-8255

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Daytime with Secondary nighttime

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

Jan.	7:15 AM	6:00 PM	Jul. 5:45 AM	7:30 PM
Feb.	7:15 AM	6:15 PM	Aug. 6:00 AM	7:15 PM
Mar.	6:45 AM	6:45 PM	Sep. 6:15 AM	6:30 PM
Apr.	6:00 AM	7:00 PM	Oct. 6:30 AM	6:00 PM
Мау	5:45 AM	7:15 PM	Nov. 6:45 AM	5:45 PM
Jun.	5:30 AM	7:30 PM	Dec. 7:15 AM	5:30 PM

Permit No.: BP-20150120AIX Callsign: WSRQ Name of Permittee: LAKE ERIE COLLEGE OF OSTEOPATHIC MEDICINE, INC. Station Location: SARASOTA, FL Frequency (kHz): 1220 Station Class: D Antenna Coordinates: Day Latitude: Ν 27 Deg 28 Min 32 Sec 82 Deg 32 Min Longitude: W 08 Sec Night Latitude: Ν 27 Deg 28 Min 32 Sec W 82 Deg 32 Min 08 Sec Longitude: Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules. Nominal Power (kW): Day: 1.0 Night: 0.004 Antenna Mode: Day: DA Night: DA (DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours) Antenna Registration Number(s): Day: Tower No. ASRN 43.6 1 None 2 43.6 None Night: Tower No. ASRN 1 None 43.6 43.6 2 None

RQ			P	ermit No.:	BP-20150120AIX		
DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM							
l RMS (mV/m,	/km): Day:	299	Night:	18.9			
MS (mV/m/km)	: Day:	314.1	Night:	22.5			
RMS (mV/m/kn	ı):						
	Day:		Night:				
al Paramete	rs:						
tional Ante	nna:						
		Spacing (Deg.)			(Deg.)		
1.0000	0.000	0.0000	0.000	0	62.6		
1.0000 -13	39.000	70.0000	180.000	0	62.6		
<pre>0 = Spacing and orientation from reference tower 1 = Spacing and orientation from previous tower Theoretical Parameters:</pre>							
Night Directional Antenna:							
		Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)		
1.0000	0.000	0.0000	0.000	0	62.6		
1.0000 -13	39.000	70.0000	180.000	0	62.6		
pacing and c	prientatio						
	l RMS (mV/m/ MS (mV/m/km) RMS (mV/m/km) RMS (mV/m/km) ral Paramete tional Ante: Field Ph Ratio 1.0000 -13 eference Swi pacing and co pacing and co rectional An Field Ph Ratio 1.0000 -13 eference Swi pacing and co	N OF DIRECTIONAL ANTE 1 RMS (mV/m/km): Day: MS (mV/m/km): Day: RMS (mV/m/km): Day: cal Parameters: ctional Antenna: Field Phasing S Ratio (Deg.) 1.0000 -139.000 1.0000 -139.000 eference Switch pacing and orientatic pacing and orientatic cal Parameters: rectional Antenna: Field Phasing S Ratio (Deg.) 1.0000 0.000 1.0000 -139.000 cal Parameters: rectional Antenna: Field Phasing S Ratio (Deg.) 1.0000 0.000 1.0000 -139.000 ceference Switch pacing and orientatic	N OF DIRECTIONAL ANTENNA SYS 1 RMS (mV/m/km): Day: 299 MS (mV/m/km): Day: 314.1 RMS (mV/m/km): Day: cal Parameters: ctional Antenna: Field Phasing Spacing Ratio (Deg.) (Deg.) 1.0000 -139.000 70.0000 eference Switch pacing and orientation from pacing and orientation from 1.0000 -139.000 70.0000 1.0000 -139.000 70.0000 pacing and orientation from	N OF DIRECTIONAL ANTENNA SYSTEM 1 RMS (mV/m/km): Day: 299 Night: MS (mV/m/km): Day: 314.1 Night: RMS (mV/m/km): Day: Night: val Parameters: stional Antenna: Field Phasing Spacing Orientation Ratio (Deg.) (Deg.) (Deg.) 1.0000 0.000 0.0000 0.0000 1.0000 -139.000 70.0000 180.000 eference Switch pacing and orientation from reference tow pacing and orientation from previous towe tal Parameters: rectional Antenna: Field Phasing Spacing Orientation Ratio (Deg.) (Deg.) (Deg.) 1.0000 0.000 0.0000 0.000 1.0000 -139.000 70.0000 180.000 eference Switch pacing and orientation from reference towers tal Parameters: Pactional Antenna: Field Phasing Spacing Orientation Ratio (Deg.) (Deg.) (Deg.) 1.0000 0.000 0.0000 0.0000 1.0000 -139.000 70.0000 180.000 eference Switch pacing and orientation from reference towers Pacing and Pacing Paci	N OF DIRECTIONAL ANTENNA SYSTEM 1 RMS (mV/m/km): Day: 299 Night: 18.9 MS (mV/m/km): Day: 314.1 Night: 22.5 RMS (mV/m/km): Day: Night: al Parameters: stional Antenna: Field Phasing Spacing Orientation Tower Ref Ratio (Deg.) (Deg.) (Deg.) Switch * 1.0000 0.000 0.0000 0.000 0 1.0000 -139.000 70.0000 180.000 0 eference Switch pacing and orientation from reference tower pacing and orientation from previous tower stal Parameters: sectional Antenna: Field Phasing Spacing Orientation Tower Ref Ratio (Deg.) (Deg.) (Deg.) Switch * 1.0000 0.000 0.0000 0.000 0 1.0000 -139.000 70.000 180.000 0 1.0000 -139.000 70.000 180.000 0		

Inverse Distance Field Strength: The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:	
54	11.08	mV/m
306	11.08	mV/m

Special operating conditions or restrictions:

- The permittee must submit a proof of performance as set forth in either 1 Section 73.151(a) or 73.151(c) of the rules before program tests are authorized. A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the day directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules. Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 3 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 4 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.
- Before program tests are authorized, sufficient data shall be 5 submitted to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations WSRQ and WWPR(ID# 60587) and there shall be filed with the license application copies of a firm agreement entered into by the two stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, both stations shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.

Special operating conditions or restrictions:

- Prior to construction of the tower authorized herein, permittee shall 6 notify AM Station WWPR (ID# 60587) so that, if necessary that AM station: may determine operating power by a method described in Section 73.51(a)(1) or (d), and/or request temporary authority from the Commission in Washington, D.C. to operate with parameters at variance in order to maintain monitoring point field strengths within authorized limits. Permittee shall be responsible for installation and continued maintenance of detuning apparatus necessary to prevent adverse effects upon the radiation pattern of the AM station. Both prior to construction of the tower and subsequent to the installation of all appurtenances thereon, a partial proof of performance, as defined by Section 73.154(a) of the Commission's Rules, shall be conducted to establish that the AM array has not been adversely affected and prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission.
- 7 Ground system consists of 120 equally spaced, buried, copper radials about the base of the existing WWPR tower, each 50.3 meters in length (61.4 meters about the base of the new second WSRQ tower) except where intersecting radials are shortened and bonded to a transverse copper strap midway between the adjacent towers.

\*\*\* END OF AUTHORIZATION \*\*\*