

United States of America FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

LONG C		MMUNICATIONS,	LLC.
PO BC	X	1059	

HICKORY NC 28603

Son Nguyen Supervisory Engineer Audio Division

Media Bureau

Grant Date: June 05, 2001

This permit expires 3:00 a.m. local time, 36 months after the

grant date specified above.

Facility Id: 65918

Call Sign: WHKY

Permit File Number: BP-20000515ABL

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

Jan.	7:30 AM	5:30 PM	Jul. 5:15 AM	7:45 PM
Feb.	7:15 AM	6:00 PM	Aug. 5:45 AM	7:15 PM
Mar.	6:30 AM	6:30 PM	Sep. 6:00 AM	6:30 PM
Apr.	6:00 AM	7:00 PM	Oct. 6:30 AM	5:45 PM
Мау	5:15 AM	7:30 PM	Nov. 7:00 AM	5:15 PM
Jun.	5:15 AM	7:45 PM	Dec. 7:30 AM	5:15 PM

Permit No.: BP-20000515ABL Callsign: WHKY Name of Permittee: LONG COMMUNICATIONS, LLC. Station Location: HICKORY, NC Frequency (kHz): 1290 Station Class: B Antenna Coordinates: Day Latitude: Ν 35 Deg 43 Min 35 Sec 81 Deg 18 Min Longitude: W 02 Sec Night Latitude: Ν 35 Deg 43 Min 35 Sec W 81 Deg 18 Min 02 Sec Longitude: Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules. Nominal Power (kW): Day: 25.0 Night: 1.0 Antenna Mode: Day: DA Night: DA (DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours) Antenna Registration Number(s): Day: Tower No. ASRN Overall Height (m) 1 1019099 2 1019100 3 1019101 1019102 4 Night: Tower No. ASRN Overall Height (m) 1 1019099 2 1019100 1019101 3 1019102 4

Callsign: WH	IKY			P	ermit No.:	BP-20000515AB	۶L
DESCRIPTIO	DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM						
Theoretical RMS (mV/m/km): Day: 1411 Night: 321.9							
Standard H	RMS (mV/m	/km): Da	ay: 1483				
Augmented	RMS (mV/r	m/km):		Night	:338.6		
Q Factor:		Da	ay:	Night:			
Theoreti	cal Param	eters:					
Day Dire	ctional A	ntenna:					
Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)	
1	1.0000	0.000	0.0000	0.000	0	TL/S	
2	1.2070	14.700	135.0000	357.000	0	TL/S	
3	0.9200	-39.800	190.9000	312.000	0	TL/S	
4	0.5470	-41.800	135.0000	267.000	0	TL/S	
<pre>0 = Spacing and orientation from reference tower 1 = Spacing and orientation from previous tower Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)</pre>							
Tower No	. A	В	С	D			
1	96.8	28.00	.00	.00			
2	96.8	28.00	.00	.00			
3	96.8	28.00	.00	.00			
4	96.8	28.00	.00	.00			
Theoretical Parameters:							
Night Directional Antenna:							
Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)	
1	1.0000	0.000	0.0000	0.000	0	96.8	
2	0.8000	68.000	135.0000	357.000	0	96.8	
3	0.7200	248.000	190.9000	312.000	0	96.8	
4	0.9000	180.000	135.0000	267.000	0	96.8	

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Augmentation Parameters:

Aug No.	Central Azimuth (Deg. T)	Span (Deg.)	Radiation at Central Azimuth (mV/m @ 1 km)
1	41.0	68.0	86.90
2	41.0	10.0	103.00

Callsign: WHKY

Augmentation Parameters:

Aug No.	Central Azimuth (Deg. T)	Span (Deg.)	Radiation at Central Azimuth (mV/m @ 1 km)
3	169.0	10.0	98.17
4	177.0	10.0	32.99
5	183.0	10.0	77.81
6	300.0	10.0	193.12
7	332.0	12.0	55.52

Inverse Distance Field Strength: The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:	
67	520.6	mV/m
99	658.3	mV/m
111.5	649.8	mV/m
140	834.2	mV/m

Special operating conditions or restrictions:

- 1 The permittee/licensee must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.
- 2 A complete nondirectional proof of performance, in addition to a complete proof on the day directional antenna system, shall be submitted before program tests are authorized. The nondirectional and directional field strength measurements must be made under similar environmental conditions.
- 3 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.

Special operating conditions or restrictions:

- Before program test authority is authorized by the Commission: sufficient radiofrequency (RF) electromagnetic field measurements taken at the tower fence shall be submitted to show that the new power level RF radiation is in compliance with the American National Standards Institute Guidelines (OET Bulletin No. 65. August 1997); or a fence must be erected at such distances and in such a manner as to prevent the exposure human exposure to radiofrequency electromagnetic fields in excess of the FCC Guidelines (OET Bulletin No. 65. Edition 97-01, August 1997). The fence must be of a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard. Permittee shall submit documentation of compliance with this special operating condition along with the Form 302, application for license and the request for program test authority.
- 5 Before program tests are authorized, permittee shall submit sufficient current distribution measurement data to establish clearly that the current distribution approximates that of a daytime antenna with electrical height of 124.8 degrees, as proposed.

*** END OF AUTHORIZATION ***