United States of America

FEDERAL COMMUNICATIONS COMMISSION

AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

AUBURN BROADCASTING, INC.
3568 LENOX ROAD
GENEVA NY 14456

Son Nguyen
Supervisory Engineer
Audio Division
Media Bureau

Grant Date: December 07, 2015

This permit expires 3:00 a.m. local time, 36 months after the grant date specified above.

Facility Id: 43791

Call Sign: WAUB

Permit File Number: BP-20150123AHG

Permit to propose new daytime pattern using licensed nighttime pattern at reduced power.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
Local Standard Time (Non-Advanced)

Jan.	7:30 AM	5:00 PM	Jul.	4:45 AM	7:45 PM
Feb.	7:00 AM	5:30 PM	Aug.	5:15 AM	7:15 PM
Mar.	6:15 AM	6:15 PM	Sep.	5:45 AM	6:15 PM
Apr.	5:30 AM	6:45 PM	Oct.	6:15 AM	5:30 PM
May	4:45 AM	7:15 PM	Nov.	7:00 AM	4:45 PM
Jun.	4:30 AM	7:45 PM	Dec.	7:30 AM	4:30 PM

Name of Permittee: AUBURN BROADCASTING, INC.

Station Location: AUBURN, NY

Frequency (kHz): 1590

Station Class: B

Antenna Coordinates:

		Day				
Latitude:	N	42	Deg	54	Min	34 Sec
Longitude:	W	76	Deg	36	Min	09 Sec

		Night				
Latitude:	N	42	Deg	54	Min	34 Sec
Longitude:	W	76	Deg	36	Min	09 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 0.45 Night: 1.0

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No.	ASRN	
1	None	48
2	None	48
3	None	48

Night:

Tower No.	ASRN	
1	None	48
2	None	48
3	None	48

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 223.24 Night: 332.79

Standard RMS (mV/m/km): Day: 234.63 Night: 349.66

Augmented RMS (mV/m/km):

Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	90.0
2	1.9390	-142.600	90.0000	350.000	0	90.0
3	1.0000	-285.000	180.0000	350.000	0	90.0

* Tower Reference Switch
0 = Spacing and orientation from reference tower
1 = Spacing and orientation from previous tower

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	90.0
2	1.9390	-142.600	90.0000	350.000	0	90.0
3	1.0000	-285.000	180.0000	350.000	0	90.0

* Tower Reference Switch
0 = Spacing and orientation from reference tower
1 = Spacing and orientation from previous tower

Inverse Distance Field Strength:
The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:	
95	10.5	mV/m
115	10.5	mV/m
125	10.5	mV/m
245	10.5	mV/m

Special operating conditions or restrictions:

1 The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.
A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (day) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.
Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).

2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.

3 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.

4 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.

5 Ground system consists of 120 equally spaced, buried, copper radials, each 47.1 meters in length except where terminated by property boundaries or where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers, plus a copper ground screen 14.6 meters square, about the base of each tower.

*** END OF AUTHORIZATION ***