



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

WASHINGTON BROADCASTING COMPANY
98 SOUTH MAIN STREET
WASHINGTON PA 15301

Robert D. Greenberg
Supervisory Engineer
Audio Division
Media Bureau

Facility ID: 70944

Grant Date: May 11, 1992

Call Sign: WJPA-FM

This permit expires 3:00 a.m.
local time, November 11, 1993.

Permit File Number: BPH-19900627IC

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: WASHINGTON BROADCASTING COMPANY

Station Location: PA-WASHINGTON

Frequency (MHz): 95.3

Channel: 237

Class: A

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna Coordinates: North Latitude: 40 deg 11 min 23 sec
West Longitude: 80 deg 14 min 02 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW):	4.2	4.2
Height of radiation center above ground (Meters):	89	89
Height of radiation center above mean sea level (Meters):	481	481
Height of radiation center above average terrain (Meters):	117	117

Antenna structure registration number: Not Required

Overall height of antenna structure above ground: 93 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

None Required

Special operating conditions or restrictions:

- During installation of the antenna authorized herein, AM Station(s) listed below shall determine operating power by the indirect method. Upon completion of the installation, antenna impedance measurements on the AM antenna shall be made and, prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission (along with a tower sketch of the installation) in an application for the AM station to return to the direct method of power determination.
(Revised January 28, 1983)
WJPA (AM)

Special operating conditions or restrictions:

- 2 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- 3 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit an affidavit from a licensed surveyor to establish that the directional antenna has been oriented at the proper azimuth.

Special operating conditions or restrictions:

4 .
 The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit.
 .
 A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power:
 .
 4.2 kilowatts
 .
 Principal minima and their associated field strength limits:
 .
 .
 40 degrees True: 2.14 kilowatts
 90 degrees True: 2.06 kilowatts
 .
 .
 The automatic program test provisions of 47 CFR Section 73.1620 do not apply in this case. A formal request for program test authority must be filed in conjunction with FCC Form 302, Application for License, before program tests will be authorized. This request should be made at least 10 days prior to the date on which program tests are desired to commence. This request must contain documentation which demonstrates compliance with the following special operating condition:
 .
 .
 Permittee shall submit a statement certifying that a fence has been constructed at least 3 meters from the base of the tower and in such a manner as to prevent the exposure of humans to radiofrequency radiation in excess of the American National Standards Institute Guidelines in OST Bulletin No. 65, October 1985. The fence must be of a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard.
 .
 Documentation demonstrating compliance with the special operating condition may be submitted in advance of the filing FCC Form 302. The Commission's staff will review it for compliance and respond by letter stating whether automatic Program test authority has been reinstated.
 .
 .
 ***** THIS IS A SECTION 73.215 CONTOUR PROTECTION GRANT *****
 ***** AS REQUESTED BY THIS APPLICANT *****

*** END OF AUTHORIZATION ***