



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

BEASLEY MEDIA GROUP LICENSES, LLC
3033 RIVIERA DRIVE
SUITE 200
NAPLES FL 34103

Son Nguyen
Supervisory Engineer
Audio Division
Media Bureau

Facility Id: 54686

Call Sign: KDWN

Permit File Number: BP-20190531AAN

Grant Date: October 08, 2019

This permit expires 3:00 a.m.
local time, 36 months after the
grant date specified above.

Permit to change site, antenna systems and co-locate with station
KXST(AM).

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
Local Standard Time (Non-Advanced)

Jan.	6:45 AM	4:45 PM	Jul.	4:30 AM	7:00 PM
Feb.	6:30 AM	5:15 PM	Aug.	5:00 AM	6:30 PM
Mar.	5:45 AM	5:45 PM	Sep.	5:15 AM	5:45 PM
Apr.	5:15 AM	6:15 PM	Oct.	5:45 AM	5:00 PM
May	4:30 AM	6:45 PM	Nov.	6:15 AM	4:30 PM
Jun.	4:15 AM	7:00 PM	Dec.	6:45 AM	4:30 PM

Callsign: KDWN

Permit No.: BP-20190531AAN

Name of Permittee: BEASLEY MEDIA GROUP LICENSES, LLC

Station Location: LAS VEGAS, NV

Frequency (kHz): 720

Station Class: B

Antenna Coordinates:

Day

Latitude: N 36 Deg 16 Min 04 Sec

Longitude: W 115 Deg 02 Min 42 Sec

Night

Latitude: N 36 Deg 16 Min 04 Sec

Longitude: W 115 Deg 02 Min 42 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 25.0 Night: 7.5

Antenna Mode: Day: ND Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No.	ASRN	Overall Height (m)
1	1291307	

Night:

Tower No.	ASRN	Overall Height (m)
1	1058337	
2	1291307	
3	1058338	

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Night: 812.9
 Standard RMS (mV/m/km): Night: 854
 Augmented RMS (mV/m/km):
 Q Factor: Night:

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	63.3
2	1.1000	246.500	53.4000	209.200	0	77.2
3	0.4500	15.500	122.3000	129.100	0	63.3

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Non-Directional Antenna: Day

Radiator Height: 89.3 meters; 77.2 deg

Theoretical Efficiency: 297.6 mV/m/kw at 1km

Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Night:

Azimuth: Radiation:
 74 48.97 mV/m

Special operating conditions or restrictions:

- 1 The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.
A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (night) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.
Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 3 Before program tests are authorized, sufficient data shall be submitted to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations KDWN and KXST (ID#47745) and there shall be filed with the license application copies of a firm agreement entered into by the two stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, both stations shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.
- 4 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 5 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.

Special operating conditions or restrictions:

- 6 Ground system consists of 120 equally spaced, buried, copper radials, about the base of each tower, each 65.7 meters in length around nighttime towers #1(N) and #3(E), and 89.2 meters around daytime/nighttime tower #2(W), except where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers, plus 120 interspersed radials 15.2 meters in length around nighttime towers #1(N) and #3(E), and 7.3 meters around daytime/nighttime tower #2(W).

*** END OF AUTHORIZATION ***