



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

OZCAT ENTERTAINMENT
1026 GEORGIA STREET
VALLEJO CA 94590

Arthur E. Doak
Senior Engineer
Audio Division
Media Bureau

Facility ID: 174017

Grant Date: May 20, 2016

Call Sign: KZCT

The authority granted herein has no effect on the expiration date of the underlying construction permit.

Permit File Number: BMPED-20160425ACK

This permit modifies Permit No.: BPED-20140429AVA

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: OZCAT ENTERTAINMENT

Station Location: CA-VALLEJO

Frequency (MHz): 89.5

Channel: 208

Class: A

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna Coordinates: North Latitude: 38 deg 06 min 05 sec
West Longitude: 122 deg 14 min 41 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW):		.90
Height of radiation center above ground (Meters):		29
Height of radiation center above mean sea level (Meters):		44
Height of radiation center above average terrain (Meters):		-5

Antenna structure registration number: Not Required

Overall height of antenna structure above ground: 29 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

None Required

Special operating conditions or restrictions:

- 1 The permittee/licensee, in coordination with other users of the site, must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of the FCC guidelines.

Special operating conditions or restrictions:

- 2 THE AUTOMATIC PROGRAM TEST PROVISIONS OF 47 C.F.R. § 73.1620 DO NOT APPLY IN THIS CASE. A FORMAL REQUEST FOR PROGRAM TEST AUTHORITY MUST BE FILED WITH THE FCC FORM 302-FM, APPLICATION FOR LICENSE, BEFORE PROGRAM TESTS WILL BE AUTHORIZED. This request must contain documentation which demonstrates compliance with the following special operating condition:
- 3 The permittee/licensee must, upon completion of construction and during the equipment test period, make proper radiofrequency electromagnetic (RF) field strength measurements throughout the transmitter site area, including on the roof and inside all nearby buildings, to determine if there are any areas that exceed the FCC guidelines for human exposure to RF fields. Any areas, including on the roof or inside a building, found to exceed the recommended guidelines must be clearly marked with appropriate visual warning signs which describe the nature of the hazard. Furthermore, access to these areas must be restricted. If necessary, a fence must be erected at such distances and in such a manner as to prevent the exposure of humans to RF fields in excess of the FCC Guidelines (OET Bulletin No. 65, Edition 97-01, August 1997). The fence must be a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard. Any areas within the fence found to exceed the recommended guidelines must be clearly marked with appropriate visual warning signs.
- 4 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit the results of a complete proof-of-performance to establish the horizontal plane radiation pattern for the vertically polarized only radiation component. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits must include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- 5 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit a certification executed by a licensed surveyor showing that the FM directional antenna system has been oriented at the azimuth(s) specified in the directional antenna proof of performance. This certification must include a description of the method used by the surveyor to determine the azimuth(s) of the installed directional antenna system and the accuracy of that determination.
- 6 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit must include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifications of the certifying engineer.
- 7 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an exhibit demonstrating that the measured directional antenna pattern complies with the appropriate community coverage requirements of 47 C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. § 73.316(c)(2)(ix)(B)).

Special operating conditions or restrictions:

- 8 The RMS of the measured relative field horizontal plane directional antenna pattern must encompass at least 85% of the RMS of the relative field horizontal plane directional antenna pattern authorized by this construction permit.

- 9 The relative field strength of the measured vertically polarized only radiation component shall not exceed at any azimuth the value indicated on the radiation pattern authorized by this construction permit.

A relative field strength of 1.0 on the radiation pattern herein authorized corresponds to the following effective radiated power:

0.9 kilowatt (vertically polarized only)

Principal minima and their associated field strength limits:

160 to 170 degrees True (clockwise): 0.03 kilowatt (vertically polarized only)

*** END OF AUTHORIZATION ***