



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION LICENSE

Authorizing Official:

Official Mailing Address:

Good Karma Broadcasting, L.L.C.
301 W Wisconsin Avenue
Suite 200
Milwaukee WI 53203

Son Nguyen
Supervisory Engineer
Audio Division
Media Bureau

Facility Id: 65636

Call Sign: WEPN

License File Number: BZ-20051017ADH

Grant Date: January 19, 2006

This license expires 3:00 a.m.
local time, June 01, 2006.

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
Local Standard Time (Non-Advanced)

Jan.	7:15 AM	5:00 PM	Jul.	4:30 AM	7:30 PM
Feb.	6:45 AM	5:30 PM	Aug.	5:00 AM	7:00 PM
Mar.	6:15 AM	6:00 PM	Sep.	5:30 AM	6:00 PM
Apr.	5:15 AM	6:30 PM	Oct.	6:00 AM	5:15 PM
May	4:45 AM	7:00 PM	Nov.	6:45 AM	4:45 PM
Jun.	4:30 AM	7:30 PM	Dec.	7:15 AM	4:30 PM

Callsign: WEPN

License No.: BZ-20051017ADH

Name of Licensee: Good Karma Broadcasting, L.L.C.

Station Location: NEW YORK, NY

Frequency (kHz): 1050

Station Class: B

Antenna Coordinates:

Day

Latitude: N 40 Deg 48 Min 26 Sec

Longitude: W 74 Deg 04 Min 11 Sec

Night

Latitude: N 40 Deg 48 Min 26 Sec

Longitude: W 74 Deg 04 Min 11 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 50.0 Night: 50.0

Antenna Input Power (kW): Day: 52.6 Night: 52.6

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Current (amperes): Day: 32.45 Night: 32.45

Resistance (ohms): Day: 50 Night: 50

Antenna Registration Number(s):

Day:

Tower No.	ASRN	Overall Height (m)
1	1045787	
2	1045786	
3	1045785	

Night:

Tower No.	ASRN	Overall Height (m)
1	1045787	
2	1045786	
3	1045785	

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 2758.42 Night: 2758.42

Standard RMS (mV/m/km):

Augmented RMS (mV/m/km): Day: 3139.8 Night: 3139.8

Q Factor: Day: 70.711 Night: 70.711

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	186.0
2	0.5490	85.300	90.0000	262.000	0	186.0
3	0.5980	-54.400	120.0000	60.000	0	186.0

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Augmentation Parameters:

Aug No.	Central Azimuth (Deg. T)	Span (Deg.)	Radiation at Central Azimuth (mV/m @ 1 km)
1	23.0	59.0	4330.26
2	59.0	48.0	4451.93
3	83.0	48.0	4444.96
4	107.0	43.0	4529.11
5	128.5	43.0	4444.96
6	150.0	43.0	3626.79
7	203.0	20.0	434.52
8	213.0	17.0	305.78
9	221.5	17.0	292.90
10	230.0	17.0	292.90
11	240.0	20.0	294.51
12	250.0	20.0	292.90
13	260.0	20.0	321.87
14	270.0	20.0	452.23
15	297.0	54.0	1181.85
16	324.0	54.0	2344.46
17	353.5	59.0	3840.97

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	1.0000	0.000	0.0000	0.000	0	186.0
2	0.5490	85.300	90.0000	262.000	0	186.0
3	0.5980	-54.400	120.0000	60.000	0	186.0

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Augmentation Parameters:

Aug No.	Central Azimuth (Deg. T)	Span (Deg.)	Radiation at Central Azimuth (mV/m @ 1 km)
1	23.0	59.0	4330.26
2	59.0	48.0	4451.93
3	83.0	48.0	4444.96
4	107.0	43.0	4529.11
5	128.5	43.0	4444.96
6	150.0	43.0	3626.79
7	203.0	20.0	434.52
8	213.0	17.0	305.78
9	221.5	17.0	292.90
10	230.0	17.0	292.90
11	240.0	20.0	294.51
12	250.0	20.0	292.90
13	260.0	20.0	321.87
14	270.0	20.0	452.23
15	297.0	54.0	1181.85
16	324.0	54.0	2344.46
17	353.5	59.0	3840.97

Day Directional Operation:

Twr. No.	Phase (Deg.)	Antenna Monitor Sample Current Ratio
1	89.6	0.239
2	0	1
3	-78.4	0.904

Night Directional Operation:

Twr. No.	Phase (Deg.)	Antenna Monitor Sample Current Ratio
1	89.6	0.239
2	0	1

Night Directional Operation:

Tw. Phase	Antenna Monitor
No. (Deg.)	Sample Current Ratio
3 -78.4	0.904

Antenna Monitor: POTOMAC INSTRUMENTS AM-1901

Sampling System Approved Under Section 73.68 of the Rules.

Monitoring Points:

Day Operation:

Radial (Deg. T)	Distance From Transmitter (kM)	Maximum Field Strength (mV/m)
213	6.53	97.12
230	6.74	64.43
250	6.47	19.85
270	2.82	230.8

Night Operation:

Radial (Deg. T)	Distance From Transmitter (kM)	Maximum Field Strength (mV/m)
213	6.53	97.12
230	6.74	64.43
250	6.47	19.85
270	2.82	230.8

Special operating conditions or restrictions:

- 1 The permittee/licensee must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

Special operating conditions or restrictions:

2 Direction of and Field Intensity at Monitoring Points:

Direction of 213 degrees true North. From the transmitter site drive right (North) on N.J. Route 120, 0.6km (0.35 mile) to second right (East) turn at "Arena RaceTrack Stadium". Turn right (East) and continue across the Route 120 over pass and then North (straight) 0.9km (0.55 mile) bearing right (East) again on to Route 120 (South). Drive south on Route 120, 0.6 km (0.35 mile) and take the Route 3 West exit to Clifton (Right).

Continue west on Route 3, 3.2km (2.0 miles) to the Ridge exit on the right (North). Take this exit and turn left (South) on Ridge Road 4.3 km (2.7 miles) to Belleville Turnpike. Turn left (Southeast) on Belleville Turnpike 3.7 km (2.3 miles) just over a railroad overpass. Park at concrete bridge over ditch. Walk 200 paces west along the north side of this overpass to railroad tracks. Walk right (North) 90 paces along track to the 213 degrees Monitor Point.

Direction of 230 degrees true North. From the transmitter site drive right (North) on NJ Route 120, 0.6 km (0.35) mile to second right (East) turn at "Arena Racetrack Stadium". Turn right (East) and continue across the route 120 overpass and then North (straight) 0.9 km (0.55 mile) bearing right (East) again on to Route 120, 0.6km (0.35 mile) and take Route 3 West exit to Clifton (right).

Continue West on route 3, 3.2 km (2.0 miles) to the Ridge Road exit on the right (North). Take this exit and turn left (South) on Ridge Road 4.3 km (2.7 miles) to Belleville Turnpike. Turn left (Southeast) on Belleville Turnpike 1.7 km (1.0 mile) to Sellers Street. Turn right (Southwest) on Sellers Street and proceed 0.4 km (0.24 mile) to manhole in center of street, in front of #48 Sellers Street.

3 Direction of 250 degrees true North. The measurement point is located at the intersection of William Street and Riverview Avenue on the corner of the street marker sign.

Direction of 270 degrees true North. From the 213 degrees Monitor Point return west along Belleville Turnpike 2.9 km (1.8 miles) to Schuyler road at shopping enter. Turn right (North) on Schuyler 3.1 km (1.9 miles) around bend and right (North) onto Highway 11, 0.5 km (0.3mile) to Valley Brook Avenue at stoplight. Turn right (southeast) on Valley Brook 1.1 km (0.7 mile) to intersection with Clay Street. Turn left (Northwest) on Clay for 0.6 km (0.4 mile) to triangle island at Clay and Wall Street. Turn right at intersection and enter parking lot. The 270 degrees Monitor Point is just opposite the East Corner of the Y shaped brick building on the west edge of this parking lot at "Fire Zone" sign opposite No. 1099.

Ground System:

Ground System consists of : 120-79.2 m equally spaced, buried copper radials, plus 120-7.6 m equally spaced, elevated radials terminated in a bounding ring which is bonded to a similar ring at ground level to which the ground radials are bonded. Intersecting radials are shortened and bonded to transverse copper strap midway between adjacent towers.

*** END OF AUTHORIZATION ***