



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

CAMERON BROADCASTING, INC.
2350 MIRACLE MILE ROAD
SUITE 300
BULLHEAD CITY AZ 86442

Arthur E. Doak
Senior Engineer
Audio Division
Media Bureau

Facility ID: 8385

Grant Date: June 10, 2016

Call Sign: KLUK

This permit expires 3:00 a.m.
local time, 36 months after the
grant date specified above.

Permit File Number: BPH-20160525AAS

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: CAMERON BROADCASTING, INC.

Station Location: CA-NEEDLES

Frequency (MHz): 97.9

Channel: 250

Class: C

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Non-Directional

Antenna Coordinates: North Latitude: 35 deg 02 min 04 sec
West Longitude: 114 deg 22 min 12 sec

Table with 3 columns: Parameter, Horizontally Polarized Antenna, Vertically Polarized Antenna. Rows include Effective radiated power, Height of radiation center (ground, sea level, terrain), and Antenna structure registration number.

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

None Required

Special operating conditions or restrictions:

- 1 ***** This is a Section 73.215 contour protection grant ***** as requested by this applicant *****
2 The permittee/licensee, in coordination with other users of the site, must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of the FCC guidelines.
3 THE AUTOMATIC PROGRAM TEST PROVISIONS OF 47 C.F.R. § 73.1620 DO NOT APPLY IN THIS CASE. A FORMAL REQUEST FOR PROGRAM TEST AUTHORITY MUST BE FILED WITH THE FCC FORM 302-FM, APPLICATION FOR LICENSE, BEFORE PROGRAM TESTS WILL BE AUTHORIZED. This request must contain documentation which demonstrates compliance with the following special operating condition:

Special operating conditions or restrictions:

- 4 The permittee/licensee must, upon completion of construction and during the equipment test period, make proper radiofrequency electromagnetic (RF) field strength measurements throughout the transmitter site area to determine if there are any areas that exceed the FCC guidelines for human exposure to RF fields. If necessary, a fence must be erected at such distances and in such a manner as to prevent the exposure of humans to RF fields in excess of the FCC Guidelines (OET Bulletin No. 65, Edition 97-01, August 1997). The fence must be a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard. Any areas within the fence found to exceed the recommended guidelines must be clearly marked with appropriate visual warning signs.

*** END OF AUTHORIZATION ***