



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

WHITE MOUNTAINS BROADCASTING, LLC
P.O. BOX 896
LITTLETON NH 03561

Rodolfo F. Bonacci
Assistant Chief
Audio Division
Media Bureau

Facility ID: 190383

Call Sign: WWOX

Permit File Number: BNPH-20120529AJJ

Grant Date: June 04, 2014

This permit expires 3:00 a.m.
local time, 36 months after the
grant date specified above.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: WHITE MOUNTAINS BROADCASTING, LLC

Station Location: VT-CANAAN

Frequency (MHz): 94.1

Channel: 231

Class: A

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna Coordinates: North Latitude: 44 deg 59 min 37 sec
West Longitude: 71 deg 32 min 24 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW):	.100	.100
Height of radiation center above ground (Meters):	15	15
Height of radiation center above mean sea level (Meters):	347	347
Height of radiation center above average terrain (Meters):	-146	-146

Antenna structure registration number: Not Required

Overall height of antenna structure above ground: 16 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

None Required

Special operating conditions or restrictions:

- 1 The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.
- 2 The assignment is automatically downgraded pursuant to the procedures established in the Report and Order in MM Docket 88-118, 4 FCC Rcd 2413 (1989). Accordingly, effective the grant date of this authorization, the FM assignment IS MODIFIED as follows:

Community	Channel No.
Canaan, VT	Add 231A, Delete 231C3

Special operating conditions or restrictions:

- 3 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- 4 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee must submit a certification executed by a licensed surveyor showing that the FM directional antenna system has been oriented at the azimuth(s) specified in the directional antenna proof of performance. This certification must include a description of the method used by the surveyor to determine the azimuth(s) of the installed directional antenna system and the accuracy of that determination.
- 5 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifications of the certifying engineer.
- 6 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee must submit an exhibit demonstrating that the measured directional antenna pattern complies with the appropriate community coverage provisions of 47 C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. Section 73.316(c)(2)(ix)(B)).
- 7 The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit.

A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power:

0.100 kilowatts.

Principal minima and their associated field strength limits:

70 - 100 degrees True: 0.0032 kilowatts
190 - 220 degrees True: 0.0032 kilowatts

*** END OF AUTHORIZATION ***