

Federal Communications Commission

AM BROADCAST STATION CONSTRUCTION PERMIT

Licensee/Permittee

AMC PARTNERS ESCANABA,
LLC
258 SOUTH MAIN ST.
FOND DU LAC, WI, 54935

Call Sign	Facility ID
WDMJ	24448

File Number BP-20230324AAG	This Permit Modifies License File No. BZ-20150205AEO	
Filing Date 04/07/2023	Grant Date 11/13/2023	Expiration Date 36 months after the grant date
Description Text Permit to use new shorter tower with slightly higher night power due to collapse of old taller tower.		

Community of License City: Marquette State: MI	Frequency (KHz) 1320	Station Class D	Service Type Main
Facility Type			
Hours of Operation Daytime Nighttime			
Station Antenna Modes/Antenna Types Daytime: Non-Directional Nighttime: Non-Directional			

Average Hours of Sunrise and Sunset
Local Standard Time (Non-Advanced)

Month	Sunrise	Sunset
January	8:30	17:30
February	8:00	18:15
March	7:00	19:00
April	6:00	19:30
May	5:15	20:15
June	5:00	20:45
July	5:15	20:45
August	5:45	20:00
September	6:30	19:00
October	7:00	18:00
November	7:45	17:15
December	8:30	17:00

Transmitter

Type Accepted. See Sections 73.1660, 73.1665, and 73.1670 of the Commission's Rules

Antenna Mode: Daytime

Antenna Type: Non-Directional

Antenna Coordinates (NAD 83) Latitude 46° 32' 42.8" N Longitude 87° 26' 40.5" W	Nominal Power (kW) 5.000														
Antenna Structure Registration Number(s)															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Tower No.</th> <th style="width: 25%;">ASRN</th> <th style="width: 60%;">Overall Height (m)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1007590</td> <td style="text-align: center;">60.6</td> </tr> </tbody> </table>		Tower No.	ASRN	Overall Height (m)	1	1007590	60.6								
Tower No.	ASRN	Overall Height (m)													
1	1007590	60.6													
Radiator Height 60 meters 95.0 degrees	Theoretical Efficiency 309 mV/m/kw at 1 km														
Theoretical Parameters															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Tower No.</th> <th style="width: 10%;">Field Ratio</th> <th style="width: 15%;">Phasing (deg.)</th> <th style="width: 15%;">Spacing (deg.)</th> <th style="width: 15%;">Orientation (deg.)</th> <th style="width: 15%;">Tower Ref. Switch*</th> <th style="width: 10%;">Height (deg.)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">95.0</td> </tr> </tbody> </table>		Tower No.	Field Ratio	Phasing (deg.)	Spacing (deg.)	Orientation (deg.)	Tower Ref. Switch*	Height (deg.)	1	1	0	0	0	0	95.0
Tower No.	Field Ratio	Phasing (deg.)	Spacing (deg.)	Orientation (deg.)	Tower Ref. Switch*	Height (deg.)									
1	1	0	0	0	0	95.0									
<p>* Tower Reference Switch</p> <p>0 = Spacing and orientation from reference tower</p> <p>1 = Spacing and orientation from previous tower</p>															
Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Tower No.</th> <th style="width: 15%;">Tower Type</th> <th style="width: 5%;">A</th> <th style="width: 5%;">B</th> <th style="width: 5%;">C</th> <th style="width: 5%;">D</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">Neither</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		Tower No.	Tower Type	A	B	C	D	1	Neither						
Tower No.	Tower Type	A	B	C	D										
1	Neither														

Antenna Mode: Nighttime

Antenna Type: Non-Directional

Antenna Coordinates (NAD 83) Latitude 46° 32' 42.8" N Longitude 87° 26' 40.5" W	Nominal Power (kW) 0.140														
Antenna Structure Registration Number(s)															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Tower No.</th> <th style="width: 20%;">ASRN</th> <th style="width: 65%;">Overall Height (m)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1007590</td> <td style="text-align: center;">60.6</td> </tr> </tbody> </table>		Tower No.	ASRN	Overall Height (m)	1	1007590	60.6								
Tower No.	ASRN	Overall Height (m)													
1	1007590	60.6													
Radiator Height 60 meters 95.0 degrees	Theoretical Efficiency 309 mV/m/kw at 1 km														
Theoretical Parameters															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Tower No.</th> <th style="width: 10%;">Field Ratio</th> <th style="width: 15%;">Phasing (deg.)</th> <th style="width: 15%;">Spacing (deg.)</th> <th style="width: 15%;">Orientation (deg.)</th> <th style="width: 15%;">Tower Ref. Switch*</th> <th style="width: 10%;">Height (deg.)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">0</td> <td style="text-align: center;">95.0</td> </tr> </tbody> </table>		Tower No.	Field Ratio	Phasing (deg.)	Spacing (deg.)	Orientation (deg.)	Tower Ref. Switch*	Height (deg.)	1	1	0	0	0	0	95.0
Tower No.	Field Ratio	Phasing (deg.)	Spacing (deg.)	Orientation (deg.)	Tower Ref. Switch*	Height (deg.)									
1	1	0	0	0	0	95.0									
<p>* Tower Reference Switch</p> <p>0 = Spacing and orientation from reference tower</p> <p>1 = Spacing and orientation from previous tower</p>															
Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Tower No.</th> <th style="width: 15%;">Tower Type</th> <th style="width: 5%;">A</th> <th style="width: 5%;">B</th> <th style="width: 5%;">C</th> <th style="width: 5%;">D</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">Neither</td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> <td style="text-align: center;"> </td> </tr> </tbody> </table>		Tower No.	Tower Type	A	B	C	D	1	Neither						
Tower No.	Tower Type	A	B	C	D										
1	Neither														

Special operating conditions or restrictions

The permittee /licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

- Ground system consists of 120 equally spaced, buried, copper radials about the base of the tower, each 56 meters in length.
- Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Pursuant to Section 73.3598, this Construction Permit will be subject to automatic forfeiture unless construction is complete and application for license is filed prior to expiration.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

