



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

RADIO VISION CRISTIANA MANAGEMENT CORP.
 419 BROADWAY
 PATERSON NJ 07501

Son Nguyen
 Supervisory Engineer
 Audio Division
 Media Bureau

Grant Date: May 19, 2016

Facility Id: 54874

Call Sign: WWRV

Permit File Number: BP-20131104AQW

This permit expires 3:00 a.m.
 local time, 36 months after the
 grant date specified above.

Permit to change site and patterns.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
 Local Standard Time (Non-Advanced)

Jan.	7:15 AM	5:00 PM	Jul.	4:30 AM	7:30 PM
Feb.	6:45 AM	5:30 PM	Aug.	5:00 AM	7:00 PM
Mar.	6:15 AM	6:00 PM	Sep.	5:30 AM	6:00 PM
Apr.	5:15 AM	6:30 PM	Oct.	6:00 AM	5:15 PM
May	4:45 AM	7:00 PM	Nov.	6:45 AM	4:45 PM
Jun.	4:30 AM	7:30 PM	Dec.	7:15 AM	4:30 PM

Callsign: WWRV

Permit No.: BP-20131104AQW

Name of Permittee: RADIO VISION CRISTIANA MANAGEMENT CORP.

Station Location: NEW YORK, NY

Frequency (kHz): 1330

Station Class: B

Antenna Coordinates:

Day

Latitude: N 40 Deg 50 Min 42 Sec

Longitude: W 74 Deg 01 Min 12 Sec

Night

Latitude: N 40 Deg 50 Min 42 Sec

Longitude: W 74 Deg 01 Min 12 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 10.0 Night: 3.8

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No.	ASRN	Overall Height (m)
1	1054298	
2	1058315	
3	1054299	
4	1058316	

Night:

Tower No.	ASRN	Overall Height (m)
1	1054298	
2	1058315	
3	1054299	
4	1058316	

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 1205 Night: 762.3

Standard RMS (mV/m/km): Day: 1265.8 Night: 801.4

Augmented RMS (mV/m/km):

Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.4190	32.300	0.0000	0.000	0	TL/S
2	0.9560	114.600	89.9000	327.000	0	TL/S
3	0.9740	-132.500	179.7000	327.000	0	TL/S
4	1.0000	0.000	269.6000	327.000	0	TL/S

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)

Tower No.	A	B	C	D
1	140.2	35.00	.00	.00
2	140.2	35.00	.00	.00
3	140.2	35.00	.00	.00
4	140.2	35.00	.00	.00

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.3460	54.500	0.0000	0.000	0	TL/S
2	0.9950	-153.400	89.9000	327.000	0	TL/S
3	1.0000	0.000	179.7000	327.000	0	TL/S
4	0.4480	149.300	269.6000	327.000	0	TL/S

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)

Tower No.	A	B	C	D
1	140.2	35.00	.00	.00
2	140.2	35.00	.00	.00
3	140.2	35.00	.00	.00

Top-Loaded/Sectionalized Tower Parameters: (See 47 CFR 73.160)

Tower No.	A	B	C	D
4	140.2	35.00	.00	.00

Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:
66.5	141.4 mV/m
227.5	141.4 mV/m
308.5	385.9 mV/m
345.5	385.9 mV/m

Night:

Azimuth:	Radiation:
8	83.5 mV/m
68	44.2 mV/m
226	44.2 mV/m
286	83.5 mV/m

Special operating conditions or restrictions:

- 1 The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.
 A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (day) and (night) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.
 Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).

Special operating conditions or restrictions:

- 2 Before program tests are authorized, permittee shall submit sufficient current distribution measurement data to establish clearly that the current distribution approximates that of an antenna with a total electrical height of 175.2 degrees as proposed.
- 3 Ground system consists of 120 equally spaced, buried, copper radials, each 32 to 91 meters in length except where intersecting radials are shortened and bonded to a transverse copper strap midway between adjacent towers, plus a copper ground screen 18.3 meters square, about the base of each tower.
- 4 Before program tests are authorized, sufficient data shall be submitted to show that adequate filters, traps and other equipment has been installed and adjusted to prevent interaction, intermodulation and/or generation of spurious radiation products which may be caused by common usage of the same antenna system by Stations WWRV and WZRC (ID# 27398) and there shall be filed with the license application copies of a firm agreement entered into by the two stations involved clearly fixing the responsibility of each with regard to the installation and maintenance of such equipment. In addition, field observations shall be made to determine whether spurious emissions exist and any objectionable problems resulting therefrom shall be eliminated. Following construction, and prior to authorization of program test under this grant, both stations shall each measure antenna or common point resistance and submit FCC Form 302 as application notifying the return to direct measurement of power.
- 5 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 6 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.
- 7 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.

*** END OF AUTHORIZATION ***