



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

HISPANIC TARGET MEDIA INC.
2433 E. PALO VERDE STREET
YUMA AZ 85364

Arthur E. Doak
Senior Engineer
Audio Division
Media Bureau

Facility ID: 189475

Grant Date: September 20, 2011

Call Sign: KHMJ

This permit expires 3:00 a.m.
local time, 36 months after the
grant date specified above.

Permit File Number: BNPB-20110630AGO

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: HISPANIC TARGET MEDIA INC.

Station Location: CA-TRONA

Frequency (MHz): 97.3

Channel: 247

Class: A

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna Coordinates: North Latitude: 35 deg 53 min 53 sec
 West Longitude: 117 deg 17 min 18 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW):	.285	.285
Height of radiation center above ground (Meters):	29	29
Height of radiation center above mean sea level (Meters):	1234	1234
Height of radiation center above average terrain (Meters):	453	453

Antenna structure registration number: Not Required

Overall height of antenna structure above ground: 37 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

None Required

Special operating conditions or restrictions:

- 1 The permittee/licensee, in coordination with other users of the site, must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of the FCC guidelines.

- 2 ***** This is a Section 73.215 contour protection grant *****
 ***** as requested by this applicant *****

- 3 Since the proposed FM antenna will be mounted above the existing directional antenna of co-located FM Station KRSF(FM), Ridgcrest, California (Facility ID No. 175757), the permittee must submit an exhibit including a statement from the manufacturer of KRSF's directional antenna stating that the proposed antenna will have no adverse affect on KRSF's directional antenna pattern.

Special operating conditions or restrictions:

- 4 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee/licensee must submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits must include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.
- 5 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee/licensee must submit an affidavit from a licensed surveyor to establish that the directional antenna has been oriented at the proper azimuth.
- 6 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee/licensee must submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit must include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifications of the certifying engineer.
- 7 BEFORE PROGRAM TESTS ARE AUTHORIZED, the permittee/licensee must submit an exhibit demonstrating that the measured directional antenna pattern complies with the appropriate community coverage requirements of 47 C.F.R. Sections 73.315 or 73.515 (See 47 C.F.R. § 73.316(c)(2)(ix)(B)).
- 8 The RMS of the composite measured relative field horizontal plane directional antenna pattern must encompass at least 85% of the RMS of the composite relative field horizontal plane directional antenna pattern authorized by this construction permit.
- 9 The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit.

A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power:

0.285 kilowatt

Principal minimum and its associated field strength limit:

100 degrees True: 0.013 kilowatt

*** END OF AUTHORIZATION ***