



United States of America
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

P&Y BROADCASTING CORPORATION
 3700 WILSHIRE BLVD.
 SUITE 510
 LOS ANGELES CA 90010

Son Nguyen
 Supervisory Engineer
 Audio Division
 Media Bureau

Facility Id: 61647

Call Sign: KMPC

Permit File Number: BP-20060322AAZ

Grant Date: December 19, 2006

This permit expires 3:00 a.m.
 local time, 36 months after the
 grant date specified above.

Permit to increase power and change patterns.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Hours of Operation: Unlimited

Average hours of sunrise and sunset:
 Local Standard Time (Non-Advanced)

Jan.	7:00 AM	5:00 PM	Jul.	4:45 AM	7:00 PM
Feb.	6:45 AM	5:30 PM	Aug.	5:15 AM	6:45 PM
Mar.	6:00 AM	6:00 PM	Sep.	5:30 AM	6:00 PM
Apr.	5:30 AM	6:30 PM	Oct.	6:00 AM	5:15 PM
May	4:45 AM	6:45 PM	Nov.	6:30 AM	4:45 PM
Jun.	4:45 AM	7:00 PM	Dec.	6:45 AM	4:45 PM

Callsign: KMPC

Permit No.: BP-20060322AAZ

Name of Permittee: P&Y BROADCASTING CORPORATION

Station Location: LOS ANGELES, CA

Frequency (kHz): 1540

Station Class: B

Antenna Coordinates:

Day

Latitude: N 34 Deg 04 Min 43 Sec

Longitude: W 118 Deg 11 Min 05 Sec

Night

Latitude: N 34 Deg 04 Min 43 Sec

Longitude: W 118 Deg 11 Min 05 Sec

Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Nominal Power (kW): Day: 50.0 Night: 44.0

Antenna Mode: Day: DA Night: DA

(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)

Antenna Registration Number(s):

Day:

Tower No.	ASRN	Overall Height (m)
1	1246297	
2	None	60.4
3	None	60.4
4	None	60.4
5	None	60.4
6	None	60.4

Night:

Tower No.	ASRN	Overall Height (m)
1	1246297	
2	None	60.4
3	None	60.4
4	None	60.4
5	None	60.4
6	None	60.4

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

Theoretical RMS (mV/m/km): Day: 2359 Night: 2335

Standard RMS (mV/m/km): Day: 2478 Night: 2454

Augmented RMS (mV/m/km):

Q Factor: Day: Night:

Theoretical Parameters:

Day Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.9140	111.200	0.0000	0.000	0	110.0
2	1.0000	0.000	88.9000	233.500	0	110.0
3	0.3830	-154.100	184.7000	233.500	0	110.0
4	0.1850	-33.700	137.1000	170.000	0	110.0
5	0.4850	143.100	186.6000	195.900	0	110.0
6	0.1790	72.500	257.1000	210.000	0	110.0

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Theoretical Parameters:

Night Directional Antenna:

Tower No.	Field Ratio	Phasing (Deg.)	Spacing (Deg.)	Orientation (Deg.)	Tower Ref Switch *	Height (Deg.)
1	0.6170	135.500	0.0000	0.000	0	110.0
2	1.0000	0.000	88.9000	233.500	0	110.0
3	0.5810	-128.200	184.7000	233.500	0	110.0
4	0.3250	-40.300	137.1000	170.000	0	110.0
5	0.6100	-169.400	186.6000	195.900	0	110.0
6	0.3530	50.600	257.1000	210.000	0	110.0

* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Inverse Distance Field Strength:

The inverse distance field strength at a distance of one kilometer from the above antenna in the directions specified shall not exceed the following values:

Day:

Azimuth:	Radiation:	
9	549.07	mV/m
145.5	900.49	mV/m
256	2872.19	mV/m

Night:

Azimuth:	Radiation:	
34.5	99.21	mV/m
56.5	96.33	mV/m
107	264.7	mV/m
131.5	104.68	mV/m
265	1790.27	mV/m
334.5	159.86	mV/m

Special operating conditions or restrictions:

- 1 The permittee must submit a proof of performance as set forth in either Section 73.151(a) or 73.151(c) of the rules before program tests are authorized.
A proof of performance based on field strength measurements, per Section 73.151(a), shall include a complete nondirectional proof of performance, in addition to a complete proof on the (day) and (night) directional antenna system. The nondirectional and directional field strength measurements must be made under similar environmental conditions. The proof(s) of performance submitted to the Commission must contain all of the data specified in Section 73.186 of the rules.
Permittees who elect to submit a moment method proof of performance, as set forth in Section 73.151(c), must use series-fed radiators. In addition, the sampling system must be constructed as described in Section 73.151(c) (2) (i).
- 2 Permittee shall install a type accepted transmitter, or submit application (FCC Form 301) along with data prescribed in Section 73.1660(b) should non-type accepted transmitter be proposed.
- 3 A license application (FCC Form 302) to cover this construction permit must be filed with the Commission pursuant to Section 73.3536 of the Rules before the permit expires.

Special operating conditions or restrictions:

- 4 Licensee shall be responsible for satisfying all reasonable complaints of blanketing interference within the 1 V/m contour as required by Section 73.88 of the Commission's rules.

- 5 Prior to construction of the tower authorized herein, permittee shall notify AM Station KLAC (ID# 59958) so that, if necessary that AM station: may determine operating power by a method described in Section 73.51(a) (1) or (d), and/or request temporary authority from the Commission in Washington, D.C. to operate with parameters at variance in order to maintain monitoring point field strengths within authorized limits. Permittee shall be responsible for installation and continued maintenance of detuning apparatus necessary to prevent adverse effects upon the radiation pattern of the AM station. Both prior to construction of the tower and subsequent to the installation of all appurtenances thereon, a partial proof of performance, as defined by Section 73.154(a) of the Commission's Rules, shall be conducted to establish that the AM array has not been adversely affected and prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission.

*** END OF AUTHORIZATION ***