

United States of America

FEDERAL COMMUNICATIONS COMMISSION FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Rodolfo F. Bonacci

Assistant Chief

Audio Division

Official Mailing Address:

UNIVERSITY OF ROCHESTER BROADCAST CORP.

201 WILSON COMMONS

ROCHESTER NY 14627

Media Bureau

Facility ID: 69138

Call Sign: WRUR-FM

Permit File Number: BMPED-20070907AAV

Grant Date: November 17, 2008

The authority granted herein has no effect on the expiration date of the underlying construction

permit.

This permit modifies permit no.: BPED-20061117ABO

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Callsign: WRUR-FM Permit No.: BMPED-20070907AAV

Name of Permittee: UNIVERSITY OF ROCHESTER BROADCAST CORP.

Station Location: NY-ROCHESTER

Frequency (MHz): 88.5

Channel: 203

Class: B1

Hours of Operation: Unlimited

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of

the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna Coordinates: North Latitude: 43 deg 08 min 07 sec

West Longitude: 77 deg 35 min 03 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW):	18.0	18.0
Height of radiation center above ground (Meters):	52	52
Height of radiation center above mean sea level (Meters):	257	257
Height of radiation center above average terrain (Meters):	109	109

Antenna structure registration number: 1003958

Overall height of antenna structure above ground (including obstruction lighting if any) see the registration for this antenna structure.

Special operating conditions or restrictions:

BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.

Callsign: WRUR-FM

Special operating conditions or restrictions:

2 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit an affidavit from a licensed surveyor to establish that the directional antenna has been oriented at the proper azimuth.

- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifications of the certifying engineer.
- 4 The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit.

A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power:

18.0 kilowatts.

Principal minima and their associated field strength limits:

020 degrees True: 2.90 kilowatts 250 degrees True: 3.10 kilowatts 320 degrees True: 7.50 kilowatts

- THE AUTOMATIC PROGRAM TEST PROVISIONS OF 47 C.F.R. SECTION 73.1620 DO NOT APPLY IN THIS CASE. A FORMAL REQUEST FOR PROGRAM TEST AUTHORITY MUST BE FILED IN CONJUNCTION WITH FCC FORM 302-FM, APPLICATION FOR LICENSE, BEFORE PROGRAM TESTS WILL BE AUTHORIZED. This request must contain documentation which demonstrates compliance with the following special operating condition(s):
- The permittee/licensee shall, upon completion of construction and during the equipment test period, make proper radiofrequency electromagnetic (RF) field strength measurements throughout the transmitter site area to determine if there are any areas that exceed the FCC guidelines for human exposure to RF fields. If necessary, a fence must be erected at such distances and in such a manner as to prevent the exposure of humans to RF fields in excess of the FCC Guidelines (OET Bulletin No. 65, Edition 97-01, August 1997). The fence must be a type which will preclude casual or inadvertent access, and must include signage at appropriate intervals which describe the nature of the hazard. Any areas within the fence found to exceed the recommended guidelines must be clearly marked with appropriate additional signage. Documentation demonstrating compliance with the FCC radiofrequency electromagnetic field exposure guidelines shall be submitted when filing the FCC Form 302-FM.
- 7 Documentation demonstrating compliance with the special operating condition(s) may be submitted in advance of the filing of FCC Form 302-FM.

Callsign: WRUR-FM

Special operating conditions or restrictions:

If the antenna is mounted on an existing tower that is not base-insulated or detuned at the AM frequency, the permittee shall submit a certification to this effect.

If the antenna is mounted on an existing tower that is base-insulated or detuned at the frequency of AM station WHIC, Rochester, NY, Facility ID 6641, the applicant shall notify the AM station. If necessary, the AM station may determine operating power by a method described in Section 73.51(a)(1) or (d), and/or request temporary authority from the Commission in Washington, D.C. to operate with parameters at variance in order to maintain monitoring point field strengths within authorized limits. Permittee shall be responsible for readjustment and continued maintenance of any detuning apparatus necessary to prevent adverse effects upon the radiation pattern of the AM station. Both before and after the installation of the antenna and transmission line on the tower, a partial proof of performance, as defined by Section 73.154(a) of the Commission's Rules, shall be conducted to establish that the AM array has not been adversely affected. The results of the partial proofs shall be submitted to the Commission with the application for license to cover this permit.

The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.

*** END OF AUTHORIZATION ***