

United States of America FEDERAL COMMUNICATIONS COMMISSION FM BROADCAST STATION CONSTRUCTION PERMIT

Authorizing Official:

Official Mailing Address:

SALEM COMMUNICATIONS HOLDING CORPORATION 4880 SANTA ROSA ROAD CAMARILLO CA 93012

Facility ID: 47309

Call Sign: KDIS-FM

Permit File Number: BPH-19991020AAZ

Brian J. Butler Supervisory Engineer Audio Division Media Bureau

Grant Date: February 14, 2000

This permit expires 3:00 a.m. local time, 36 months after the grant date specified above.

Subject to the provisions of the Communications Act of 1934, as amended, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this permit, the permittee is hereby authorized to construct the radio transmitting apparatus herein described. Installation and adjustment of equipment not specifically set forth herein shall be in accordance with representations contained in the permittee's application for construction permit except for such modifications as are presently permitted, without application, by the Commission's Rules.

Commission rules which became effective on February 16, 1999, have a bearing on this construction permit. See Report & Order, Streamlining of Mass Media Applications, MM Docket No. 98-43, 13 FCC RCD 23056, Para. 77-90 (November 25, 1998); 63 Fed. Reg. 70039 (December 18, 1998). Pursuant to these rules, this construction permit will be subject to automatic forfeiture unless construction is complete and an application for license to cover is filed prior to expiration. See Section 73.3598.

Equipment and program tests shall be conducted only pursuant to Sections 73.1610 and 73.1620 of the Commission's Rules.

Name of Permittee: SALEM COMMUNICATIONS HOLDING CORPORATION Station Location: AR-LITTLE ROCK Frequency (MHz): 99.5 Channel: 258 Class: A Hours of Operation: Unlimited Callsign: KDIS-FM Permit No.: BPH-19991020AAZ Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: As required to achieve authorized ERP.

Antenna type: Directional

Antenna	Coordinates:	North	Latitude:	34 deg	45 min	58 sec
		West	Longitude:	92 deq	17 min	38 sec

	Horizontally Polarized Antenna	Vertically Polarized Antenna				
Effective radiated power in the Horizontal Plane (kW) :	6.0	6.0				
Height of radiation center above ground (Meters):	121	121				
Height of radiation center above mean sea level (Meters):	197	197				
Height of radiation center above average terrain (Meters)	95	95				
Antenna structure registration number: 1202972						

Overall height of antenna structure above ground (including obstruction lighting if any) see the registration for this antenna structure.

Special operating conditions or restrictions:

- 1 During installation of the antenna authorized herein, AM Station(s) listed below shall determine operating power by the indirect method. Upon completion of the installation, antenna impedance measurements on the AM antenna shall be made and, prior to or simultaneous with the filing of the application for license to cover this permit, the results submitted to the Commission (along with a tower sketch of the installation) in an application for the AM station to return to the direct method of power determination. (Revised January 28, 1983)
 - . KJBN(AM), Little Rock, AR
- BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit the 2 results of a complete proof-of-performance to establish the horizontal plane radiation patterns for both the horizontally and vertically polarized radiation components. This proof-of-performance may be accomplished using the complete full size antenna, or individual bays therefrom, mounted on a supporting structure of identical dimensions and configuration as the proposed structure, including all braces, ladders, conduits, coaxial lines, and other appurtenances; or using a carefully manufactured scale model of the entire antenna, or individual bays therefrom, mounted on an equally scaled model of the proposed supporting structure, including all appurtenances. Engineering exhibits should include a description of the antenna testing facilities and equipment employed, including appropriate photographs or sketches and a description of the testing procedures, including scale factor, measurements frequency, and equipment calibration.

Special operating conditions or restrictions:

- 3 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee shall submit an affidavit from a licensed surveyor to establish that the directional antenna has been oriented at the proper azimuth.
- 4 BEFORE PROGRAM TESTS ARE AUTHORIZED, permittee/licensee shall submit an affidavit that the installation of the directional antenna system was overseen by a qualified engineer. This affidavit shall include a certification by the engineer that the antenna was installed pursuant to the manufacturer's instructions and list the qualifications of the certifying engineer.
- 5 The relative field strength of neither the measured horizontally nor vertically polarized radiation component shall exceed at any azimuth the value indicated on the composite radiation pattern authorized by this construction permit.

A relative field strength of 1.0 on the composite radiation pattern herein authorized corresponds to the following effective radiated power: 6.0 kilowatts.

Principal minima and their associated field strength limits:

140-170 degrees True: 3.0 kilowatts.

- 6 The permittee/licensee in coordination with other users of the site must reduce power or cease operation as necessary to protect persons having access to the site, tower or antenna from radiofrequency electromagnetic fields in excess of FCC guidelines.
- 7 Permittee shall submit a statement certifying that a fence has been constructed at least one (1) meter from the base of the tower and in such a manner as to prevent the exposure of humans to radiofrequency electromagnetic fields in excess of the FCC Guidelines in OET bulletin No. 65, Edition 97-01 August 1997. The fence must be of a type which will preclude casual or inadvertent access, and must include warning signs at appropriate intervals which describe the nature of the hazard.

*** END OF AUTHORIZATION ***