

## United States of America FEDERAL COMMUNICATIONS COMMISSION AM BROADCAST STATION LICENSE

Son Nquyen

Audio Division

Media Bureau

Authorizing Official:

Supervisory Engineer

Grant Date: June 08, 1998

This license expires 3:00 a.m.

local time, August 01, 1998.

Official Mailing Address:

RADIO LICENSE HOLDING CBC, LLC 780 JOHNSON FERRY ROAD SUITE 500 ATLANTA GA 30342

Facility Id: 32982

Call Sign: WRIE

License File Number: BZ-19980306KA

Direct Measurement of Power

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Hours of Operation: Unlimited

Average hours of sunrise and sunset: Local Standard Time (Non-Advanced)

| Jan. | jan_sunrise | jan_sunset | Jul. | jul_sunrise | jul_sunset |
|------|-------------|------------|------|-------------|------------|
| Feb. | feb_sunrise | feb_sunset | Aug. | aug_sunrise | aug_sunset |
| Mar. | mar_sunrise | mar_sunset | Sep. | sep_sunrise | sep_sunset |
| Apr. | apr_sunrise | apr_sunset | Oct. | oct_sunrise | oct_sunset |
| Мау  | may_sunrise | may_sunset | Nov. | nov_sunrise | nov_sunset |
| Jun. | jun_sunrise | jun_sunset | Dec. | dec_sunrise | dec_sunset |

```
Callsign: WRIE
                                                  License No.: BZ-19980306KA
Name of Licensee: RADIO LICENSE HOLDING CBC, LLC
Station Location: ERIE, PA
Frequency (kHz): 1260
Station Class: B
Antenna Coordinates:
Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and
73.1670 of the Commission's Rules.
Nominal Power (kW):
                         Night: 5.0
Antenna Input Power (kW): Night: 5.4
Antenna Mode:
                          Night: DA
(DA=Directional Antenna, ND=Non-directional Antenna; CH=Critical Hours)
Current (amperes):
                        Night: 10.4
Resistance (ohms):
                         Night: 50
Antenna Registration Number(s):
Night:
  Tower No.
              ASRN
                               Overall Height (m)
          1
              1026442
              1026443
          2
          3
              1026444
```

4 1026445

Callsign: WRIE

DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM Theoretical RMS (mV/m/km): Night: 769.27 Standard RMS (mV/m/km): Night: Augmented RMS (mV/m/km):

Q Factor:

Night: 28.61

Theoretical Parameters:

Night Directional Antenna:

| Tower | Field  | Phasing |          | Orientation |          | Height |
|-------|--------|---------|----------|-------------|----------|--------|
| No.   | Ratio  | (Deg.)  | (Deg.)   | (Deg.)      | Switch * | (Deg.) |
| 1     | 0.3500 | 213.400 | 0.0000   | 0.000       | 0        | 96.8   |
| 2     | 1.0000 | 0.000   | 100.0000 | 170.000     | 1        | 96.8   |
| 3     | 1.1500 | 143.100 | 100.0000 | 170.000     | 1        | 96.8   |
| 4     | 0.5400 | 286.400 | 100.0000 | 170.000     | 1        | 96.8   |

\* Tower Reference Switch

0 = Spacing and orientation from reference tower

1 = Spacing and orientation from previous tower

Augmentation Parameters:

| Aug<br>No. | Central<br>Azimuth<br>(Deg. T) | Span<br>(Deg.) | Radiation<br>at Central Azimuth<br>(mV/m @ 1 km) |
|------------|--------------------------------|----------------|--|
| 1          | 66.0                           | 10.0           | 228.53   |
| 2          | 71.0                           | 10.0           | 175.42   |
| 3          | 76.0                           | 10.0           | 120.70   |
| 4          | 82.0                           | 10.0           | 85.30  |
| 5          | 90.0                           | 10.0           | 64.37  |
| 6          | 95.0                           | 10.0           | 79.66  |
| 7          | 100.0                          | 10.0           | 80.47  |
| 8          | 105.0                          | 10.0           | 80.47  |
| 9          | 110.0                          | 10.0           | 84.49  |
| 10         | 115.0                          | 10.0           | 90.45  |
| 11         | 120.0                          | 10.0           | 88.51  |
| 12         | 125.0                          | 10.0           | 82.08  |
| 13         | 130.0                          | 10.0           | 80.47  |
| 14         | 135.0                          | 10.0           | 80.47  |
| 15         | 140.0                          | 10.0           | 74.03  |
| 16         | 145.0                          | 10.0           | 100.26   |
| 17         | 187.5                          | 35.0           | 147.25   |
| 18         | 205.0                          | 20.0           | 80.47  |
| 19         | 215.0                          | 20.0           | 80.47  |
| 20         | 225.0                          | 15.0           | 90.93  |
| 21         | 232.5                          | 15.0           | 80.47  |

Callsign: WRIE

Augmentation Parameters:

| Aug<br>No. | Central<br>Azimuth<br>(Deg. T) | Span<br>(Deg.) | Radiation<br>at Central Azimuth<br>(mV/m @ 1 km) |
|------------|--------------------------------|----------------|--|
| 22         | 240.0                          | 15.0           | 72.42  |
| 23         | 254.0                          | 18.0           | 54.72  |
| 24         | 267.0                          | 26.0           | 103.00   |
| 25         | 274.0                          | 12.0           | 212.43   |

Night Directional Operation:

|   | Phase<br>(Deg.) | Antenna Monitor<br>Sample Current Ratio |
|---|-----------------|---|
| 1 | -151            |   |
| 2 | 0               |   |
| 3 | 143.1           |   |
| 4 | -75             |   |

Antenna Monitor: POTOMAC INSTRUMENTS AM-19D (210) SERIAL #648 Sampling System Approved Under Section 73.68 of the Rules.

Monitoring Points:

Night Operation:

| Radial I<br>(Deg. T) | Distance From Transmitter<br>(kM) | Maximum Field Strength<br>(mV/m) |
|----------------------|-----------------------------------|----------------------------------|
| 82                   | 3.14                              |                                  |
| 135                  | 5.71                              |                                  |
| 170                  | 3.86                              |                                  |
| 205                  | 2.98                              |                                  |
| 245                  | 4.47                              |                                  |
|                      |                                   |                                  |

\*\*\* END OF AUTHORIZATION \*\*\*